

SKU: 21112-B3

UPC:

Features & Benefits:

Description:Heat Shrinkable Tubing, Heavy Wall, 0.4in Expanded ID, Conductor Range 6-14, 12in Tube, Black, Bag of 3



Specs

Additional Class Attributes

Container	NA
Model	Tube
Shrink Ratio	3:1

Dimensions

Cut Length	12 in
Expanded ID (IN)	0.4
Expanded ID (mm)	10.16
Height (IN)	0
Height BX (IN)	3.75
Length (IN)	0
Recovered ID (IN)	0.150 IN
Recovered Wall Thickness (IN)	0.060 IN
Weight (LB)	0.2613
Weight BX (LB)	3.008
Width (IN)	0
Width BX (IN)	6.5

Additional Technical Specifications

Dielectric Strength	500 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	3
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366942004

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.2
Mil Spec #	AMS-DTL-23053/15 CLASS 1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 486D Listed
UL File Number	E158587

Environment and Temperature

Flammability Rating	Flame Retardant per Mil Spec 23053/15
Minimum Shrink Temperature	120°C
Operating Temperature	-55°C to 100°C
Temperature Rating	-55°C to 100°C

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	6 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Voltage

Voltage Rating	600 V
----------------	-------