



SKU: 21609-B2

UPC:

Features & Benefits:

Description:Heat Shrinkable Tubing, Heavy Wall, 1-1/2in Expanded ID, Conductor Range 400-4/0, 9in Tube, Black, Bag of 2

Specs

Additional Class Attributes

Container	NA
Model	Tube
Shrink Ratio	3:1

Dimensions

Cut Length	9 in
Expanded ID (IN)	1.5
Expanded ID (mm)	38.1
Height (IN)	0
Height BX (IN)	6.75
Length (IN)	0
Recovered ID (IN)	0.500 IN
Recovered Wall Thickness (IN)	0.140 IN
Weight (LB)	0.4227
Weight BX (LB)	5.3507
Width (IN)	0
Width BX (IN)	11.375

Additional Technical Specifications

Dielectric Strength	500 V/Mil
---------------------	-----------

Material and Finish

Material	Polyolefin
----------	------------

General

Bag Quantity	2
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366971296

Testing Standards

CSA File Number	AP-100973-1
CSA Standard	C22.2 No. 198.2
Mil Spec #	AMS-DTL-23053/15 CLASS 1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 486D Listed
UL File Number	E158587

Environment and Temperature

Flammability Rating	Flame Retardant per Mil Spec 23053/15
Minimum Shrink Temperature	120°C
Operating Temperature	-55°C to 100°C
Temperature Rating	-55°C to 100°C

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	400 kcmil - 4/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	400 kcmil - 4/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------