



**SKU:** 25002

**UPC:** 0783669421026

**Features & Benefits:**

**Description:** Heat Shrinkable Tubing, Thin Wall, 1/16in Expanded ID, Conductor Range 24-30, 8ft Disk, Black

## Specs

### Additional Class Attributes

Container	Disk dispenser
Model	Tube
Shrink Ratio	2:1

### Dimensions

Cut Length	96 in
Expanded ID (IN)	0.063
Expanded ID (mm)	1.6002
Height (IN)	0.048
Height BX (IN)	5.25
Length (IN)	96
Recovered ID (IN)	0.031 IN
Recovered Wall Thickness (IN)	0.017 IN
Weight (LB)	0.7
Weight BX (LB)	7
Width (IN)	0.048
Width BX (IN)	7.25

### Additional Technical Specifications

Dielectric Strength	600 V/Mil
---------------------	-----------

### Material and Finish

Material	Polyolefin
----------	------------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
NEMA Code	0-000-1
UPC Code	78366942102

### Testing Standards

<b>CSA File Number</b>	AP-100973-1
<b>CSA Standard</b>	C22.2 No. 198.1
<b>Mil Spec #</b>	AMS-DTL-23053/5 CLASS 1
<b>Prop65 Compliance</b>	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
<b>RUS Listed</b>	Yes
<b>UL / CULUS Specification</b>	UL 224 Recognized
<b>UL File Number</b>	E158587

### Environment and Temperature

<b>Flammability Rating</b>	NA
<b>Minimum Shrink Temperature</b>	90°C
<b>Operating Temperature</b>	-55°C to 135°C
<b>Temperature Rating</b>	-55°C to 135°C

### Color

<b>Color</b>	Black
--------------	-------

### Conductor Ranges

<b>Conductor Range AL Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Stranded (Primary, run, main, line)</b>	24 Str - 30 Str
<b>Conductor Range AL Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Solid (Primary, run, main, line)</b>	24 Sol - 30 Sol
<b>Conductor Range CU Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Stranded (Primary, run, main, line)</b>	24 Str - 30 Str
<b>Conductor Range CU Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Solid (Primary, run, main, line)</b>	24 Sol - 30 Sol

### Voltage

<b>Voltage Rating</b>	600 V
-----------------------	-------