

SKU: ASK-250

UPC: 0783669008395



Features & Benefits:

Description: Above Grade Splice Kit, Dual Rated, Conductor Range 250-1, Includes (1) SPA-250 Splice and (1) Piece of Heat Shrink, UL, CSA

Specs

Additional Class Attributes

Contains DE-OX®	No
Includes	(1) SPA-250, (1) Piece of heat shrink
Number of Conductors	2
Number of Ports / Wireways	2

Dimensions

Height (IN)	1.6
Height BX (IN)	6
Height (mm)	40.64
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.18049332358933
Weight BX (LB)	8.1942
Width (IN)	4
Width BX (IN)	10.75
Width (mm)	101.6

Material and Finish

Conductor Material	Copper
Material	Polyolefin

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366900839

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E125087

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 1 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 1 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------