

SKU: ASK-2

UPC: 0783669008388

Features & Benefits:

Description: Above Grade Splice Kit, Dual Rated, Conductor Range 2-8, Includes (1) SPA-2 Splice and (1) Piece of Heat Shrink, UL, CSA



Specs

Additional Class Attributes

Contains DE-OX®	No
Includes	(1) SPA-2, (1) Piece of heat shrink
Number of Conductors	2
Number of Ports / Wireways	2

Dimensions

Height (IN)	1.6
Height BX (IN)	3.75
Height (mm)	40.64
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.0500201410800818
Weight BX (LB)	3.476
Width (IN)	4
Width BX (IN)	6.5
Width (mm)	101.6

Material and Finish

Conductor Material	Copper
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366900838

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E125087

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------