



SKU: BGRC-68

UPC: 0783669009989

Features & Benefits:

Description:Permaground Bronze Ground Rod Clamp, Conductor Range 1/0-8, Ground Rod Size 3/4in, Direct Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Conductor Range Solid with Ground Rod	NA
Conductor Range Solid with Rebar	NA
Conductor Range Str with Ground Rod	1/0 Str - 8 Str
Conductor Range Str with Rebar	NA
Conductor Size with Ground Rod	8 Str
Ground Rod Size	3/4

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	1.813
Height BX (IN)	1.875
Height (mm)	46.0502
Length (IN)	1.07
Length (mm)	27.178
Weight (LB)	0.181
Width (IN)	1.031
Width BX (IN)	4.625
Width (mm)	26.1874

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Cast bronze

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366900998

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440