

IMAGE  
COMING  
SOON

**SKU:** BRBR-10-12-P25

**UPC:** 0783669201079

**Features & Benefits:**

**Description:**ILSCON Ring Terminal, Conductor Range 10-12, 1/2in Bolt Size, Non-insulated, Yellow Color Code, Pack of 25

## Specs

### Additional Class Attributes

Conductor Entry Connection	Funnel wire Compression
Construction Type	Brazed
ILSCOs Die Index Number	D1322
Installation Tooling	ILST-22K
Installing Dies	Die Set D1322
Insulation Flared End	No
Insulation Grip	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

### Dimensions

Maximum Wire Insulation Diameter (IN)	0.252
Mounting Bolt/Stud Size (mm)	304.8

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation Material	None
	Copper

### General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366920107

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

## Testing Standards

<b>Prop65 Compliance</b>	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
<b>UL Control Number</b>	20U0
<b>UL / CULUS Specification</b>	UL/cUL 486A/B Listed
<b>UL File Number</b>	E6207

## Color

<b>Color</b>	Silver
<b>Color Code</b>	Yellow

## Conductor Ranges

<b>Conductor Range AL Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Stranded (Primary, run, main, line)</b>	NA
<b>Conductor Range AL Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Solid (Primary, run, main, line)</b>	10 Sol - 12 Sol
<b>Conductor Range CU Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Stranded (Primary, run, main, line)</b>	10 Str - 12 Str
<b>Conductor Range CU Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Solid (Primary, run, main, line)</b>	NA

## Environment and Temperature

<b>Halogen Free</b>	NA
<b>Temperature Rating</b>	NA