

IMAGE COMING SOON

SKU: BRBR-10-38-P25

UPC: 0783669200874

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Range 10-12, 3/8in Bolt Size, Non-insulated, Yellow Color Code, Pack of 25

Specs

Additional Class Attributes	
Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	D1322
Installation Tooling	ILST-22K
Installing Dies	Die Set D1322
Insulation Flared End	No
Insulation Grip	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions		
Maximum Wire Insulation Diameter (IN)	0.252	
Mounting Bolt/Stud Size (mm)	965.2	

Material and Finish	
Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General		
Bag Quantity	25	
Carton Quantity Description	STD PACK QTY 10	
Dual Rated	No	
NEMA Code	S-588-3	
UPC Code	78366920087	

Bolt and Screw Sizes	
Mounting Bolt/Stud Size	3/8



Testing Standards

Prop65 Compliance This product is in compliance with Prop65. It is not known to

contain any chemicals associated with this regulation

UL Control Number 20U0

UL / CULUS Specification UL/cUL 486A/B Listed

UL File Number E6207

Color

ColorSilverColor CodeYellow

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line) 10 Sol - 12 Sol

Conductor Range CU Solid (Secondary, tap, load) NA

Conductor Range CU Stranded (Primary, run, main, line) 10 Str - 12 Str

Conductor Range CU Stranded (Secondary, tap, load)

Conductor Range AL Solid (Primary, run, main, line)

NA

Environment and Temperature

Halogen Free NA
Temperature Rating NA