

IMAGE  
COMING  
SOON

**SKU:** BRBR-14-38-P25

**UPC:** 0783669200959

**Features & Benefits:**

**Description:** ILSCON Ring Terminal, Conductor Range 14-16, 3/8in Bolt Size, Non-insulated, Blue Color Code, Pack of 25

## Specs

### Additional Class Attributes

|                          |               |
|--------------------------|---------------|
| Conductor Entry          | Funnel wire   |
| Connection               | Compression   |
| Construction Type        | Brazed        |
| ILSCOs Die Index Number  | D1322         |
| Installation Tooling     | ILST-22K      |
| Installing Dies          | Die Set D1322 |
| Insulation Flared End    | No            |
| Insulation Grip          | No            |
| Mounting Hole Type       | Thru          |
| Number of Conductors     | 1             |
| Number of Mounting Holes | 1             |
| Tongue Type              | Ring          |

### Dimensions

|                                       |       |
|---------------------------------------|-------|
| Maximum Wire Insulation Diameter (IN) | 0.177 |
| Mounting Bolt/Stud Size (mm)          | 965.2 |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Fully Insulated    | No     |
| Insulation         | None   |
| Material           | Copper |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 25              |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366920095     |

### Bolt and Screw Sizes

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 3/8 |
|-------------------------|-----|

## Testing Standards

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>Prop65 Compliance</b>        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| <b>UL Control Number</b>        | 20U0                                                                                                                |
| <b>UL / CULUS Specification</b> | UL/cUL 486A/B Listed                                                                                                |
| <b>UL File Number</b>           | E6207                                                                                                               |

## Color

|                   |        |
|-------------------|--------|
| <b>Color</b>      | Silver |
| <b>Color Code</b> | Blue   |

## Conductor Ranges

|                                                               |                 |
|---------------------------------------------------------------|-----------------|
| <b>Conductor Range AL Solid (Secondary, tap, load)</b>        | NA              |
| <b>Conductor Range AL Stranded (Primary, run, main, line)</b> | NA              |
| <b>Conductor Range AL Stranded (Secondary, tap, load)</b>     | NA              |
| <b>Conductor Range CU Solid (Primary, run, main, line)</b>    | 14 Sol - 16 Sol |
| <b>Conductor Range CU Solid (Secondary, tap, load)</b>        | NA              |
| <b>Conductor Range CU Stranded (Primary, run, main, line)</b> | 14 Str - 16 Str |
| <b>Conductor Range CU Stranded (Secondary, tap, load)</b>     | NA              |
| <b>Conductor Range AL Solid (Primary, run, main, line)</b>    | NA              |

## Environment and Temperature

|                           |    |
|---------------------------|----|
| <b>Halogen Free</b>       | NA |
| <b>Temperature Rating</b> | NA |