



SKU: CLNF-250-12-134

UPC: 0783669651287

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 250, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-62
ILSCOs Die Index Number	I-62
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.95
Barrel Length (mm)	49.53
Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	0.805
Height BX (IN)	2
Height (mm)	20.447
Inside Diameter (IN)	0.594
Inside Diameter (mm)	15.0876
Length (IN)	5.145
Length (mm)	130.683
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	0.75
Outside Diameter (mm)	19.05
Strip Length (mm)	55.5625
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.156



Tang Thickness (mm)	3.9624
Tang Width (IN)	1.09
Tang Width (mm)	27.686
Weight (LB)	0.333
Weight BX (LB)	3.484
Width (IN)	1.09
Width BX (IN)	6.188
Width (mm)	27.686

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	250 kcmil - 1/0 Str
Flex Conductor Range	4/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965128

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Yellow

Voltage

Voltage Rating

35 kV