



SKU: CLNF-4/0-12-134

UPC: 0783669651263

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 4/0, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, Flared End, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	Yes
ILSCOs Die Catalog Number	ILD-54
ILSCOs Die Index Number	I-54
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	2.145
Barrel Length (mm)	54.483
Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	0.743
Height BX (IN)	2
Height (mm)	18.8722
Inside Diameter (IN)	0.547
Inside Diameter (mm)	13.8938
Length (IN)	5.145
Length (mm)	130.683
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Outside Diameter (IN)	0.688
Outside Diameter (mm)	17.4752
Strip Length (mm)	55.5625
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.141



Tang Thickness (mm)	3.5814
Tang Width (IN)	1
Tang Width (mm)	25.4
Weight (LB)	0.284
Weight BX (LB)	2.988
Width (IN)	1
Width BX (IN)	6.188
Width (mm)	25.4

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	4/0 Str - 1 Str
Flex Conductor Range	3/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965126

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207



Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Purple

Voltage

Voltage Rating

35 kV