



SKU: CT-3

UPC: 0783669114300

Features & Benefits:

Description: Surecrimp Copper Compression Sleeve, Conductor Size 3, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-29
ILSCOs Die Index Number	I-29
Number of Conductors	1
Sight Window	No
Slotted	No

Dimensions

Height (IN)	0.375
Height BX (IN)	2.25
Height (mm)	9.525
Inside Diameter (IN)	0.275
Inside Diameter (mm)	6.985
Length (IN)	1.75
Length (mm)	44.45
Outside Diameter (IN)	0.375
Outside Diameter (mm)	9.525
Weight (LB)	0.04
Weight BX (LB)	1.9075
Width (IN)	0.375
Width BX (IN)	5
Width (mm)	9.525

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	3 Str - 6 Str
Flex Conductor Range	4 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366911430

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV
----------------	-------