




SKU: GBL-4

UPC: 0783669960051

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 4-14, Tin Plated, UL

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Kit Hardware Part #	GBL-MH1
Number of Conductors	1
Number of Mounting Holes	1
Number of Ports / Wireways	1
Wire Orientation	NA

Dimensions

Dimension G (IN)	0.2
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.79
Height BX (IN)	3.125
Height (mm)	20.066
Length (IN)	1.1
Length (mm)	27.94
Mounting Bolt/Stud Size (mm)	254
Tang Thickness (IN)	0.12
Weight (LB)	0.024
Weight BX (LB)	2.623
Width (IN)	0.385
Width BX (IN)	3.875
Width (mm)	9.779

Material and Finish

Clamping Hardware Finish	Zinc Clear Trivalent Chromate
Clamping Hardware Material	Steel
Conductor Material	Aluminum
Connector Finish	Tin
Material	Aluminum
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-573-2
UPC Code	78366996005

Bolt and Screw Sizes

Clamping Bolt Size	1/4-28
Mounting Bolt/Stud Size	#10
Wire Binding Torque	8 AWG = 25

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	COM
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207