



SKU: GPL3903BU

UPC: 0783669945478

Features & Benefits:

Description:Permaground Copper Waterpipe Ground Clamp, Conductor Range 4/0-4, Pipe Size 1-1/4 to 2in, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Fits Pipe O.D. Range	1.66 - 2.38
NPS/IPS Pipe Size	1-1/2

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	4.102
Height BX (IN)	4.5
Height (mm)	104.1908
Length (IN)	4.333
Length (mm)	110.0582
Weight (LB)	0.725
Width (IN)	1.475
Width BX (IN)	6.875
Width (mm)	37.465

Material and Finish

Conductor Material	Copper
Connector Finish	Bronze
Insulation	NA
Material	Copper



Wire Binding Hardware Material

Silicon bronze

Additional Technical Specifications

Conductor Type

Stranded

Bolt and Screw Sizes

Clamping Bolt Size 1/4

Number of Wire Binding Screws per Port 0

Wire Binding Screw Size NA

General

Bag Quantity 1

Carton Quantity Description STD PACK QTY 10

Direct Burial Yes

Dual Rated No

NEMA Code S-573-2

UPC Code 78366994547

Testing Standards

Prop65 Compliance WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number 667P

UL / CULUS Specification UL 467 Listed

UL File Number E34440