



SKU: IK-3/0

UPC: 0783669470161

Features & Benefits:

Description: Copper Split Bolt, Conductor Range for Equal Main & Tap
3/0-2 Sol, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range for Equal Run & Tap Str	3/0 Str - 1 Str
Conductor Range for Equal Run & Tap Sol	2/0 Sol - 2 Sol
Conductor Range for Minimum Tap with Maximum Run	12 Sol
Max Conductor Copperweld - Str	7 No. 7

Dimensions

Height (IN)	1.13
Height BX (IN)	3.75
Length (IN)	2
Weight (LB)	0.287
Weight BX (LB)	7.4775
Width (IN)	1.3
Width BX (IN)	6
Wire Diameter Range Primary (IN)	0.258 - 0.470

Material and Finish

Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA
Wire Binding Torque	500

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366947016

Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 65
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	460C
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Voltage

Voltage Rating	35 kV
----------------	-------