



SKU: NB-350-12

UPC: 0783669698657

Features & Benefits:

Description: Aluminum Neutral Bar, Dual Rated, Main Conductor Range 350-6, Tap Range 4-14, 12 Tap Ports, 2 Holes, #10-32 Bolt, Tin Plated, UL, CSA

Specs

Additional Class Attributes

| | |
|--------------------------|------------|
| Connection | Mechanical |
| Mounting Hole Type | Tap |
| Number of Conductors | 4 |
| Number of Mounting Holes | 2 |
| Number of Poles | 1 |
| Number of Ports Tap | 12 |
| Replacement Part(s) | E-153 |
| Type of Accessory | NBST-2/0 |

Dimensions

| | |
|------------------------------|--------------|
| Dimension G (IN) | 0.234 |
| Dimension G (mm) | 5.9436 |
| Drive Size Main | 3/8 |
| Drive Size Tap | NA |
| Drive Type Main | Internal Hex |
| Drive Type Tap | Slotted |
| Height (IN) | 1.513 |
| Height BX (IN) | 2.25 |
| Height (mm) | 38.4302 |
| Length (IN) | 2.531 |
| Length (mm) | 64.2874 |
| Mounting Bolt/Stud Size (mm) | 26212.8 |
| Mounting Hole Diameter (IN) | 0.219 |
| Mounting Hole Diameter (mm) | 5.5626 |
| Tang Length (IN) | 0.757 |
| Tang Length (mm) | 19.2278 |
| Tang Thickness (IN) | 0.187 |
| Tang Thickness (mm) | 4.7498 |
| Tang Width (IN) | 1 |
| Tang Width (mm) | 25.4 |
| Weight (LB) | 0.534 |
| Weight BX (LB) | 1.4343 |
| Width (IN) | 4.73 |
| Width BX (IN) | 5 |
| Width (mm) | 120.142 |

Material and Finish

| | |
|--------------------------------|--------------------|
| Conductor Material | Aluminum |
| Connector Finish | Tin |
| Insulation | NA |
| Material | Aluminum |
| Wire Binding Hardware Finish | Gold Zinc Chromate |
| Wire Binding Hardware Material | Steel |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|--|----------------|
| Mounting Bolt/Stud Size | #10-32 |
| Number of Wire Binding Screws per Port | 1 |
| Wire Binding Screw Size | 1/4 |
| Wire Binding Torque | 4 - 6 AWG = 45 |

General

| | |
|-----------------------------|----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 1 |
| Dual Rated | Yes |
| NEMA Code | S-588-3 |
| UPC Code | 78366969865 |

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | LR-29601 |
| CSA Standard | C22.2 No. 65-03 |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator | IND |
| UL Control Number | NA |
| UL / CULUS Specification | UL 486A/B Recognized |
| UL File Number | E6207 |

Color

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Conductor Ranges

| | |
|--|-------------------|
| Conductor Range AL Solid (Secondary, tap, load) | 10 Sol - 14 Sol |
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | 4 Str - 14 Str |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | 10 Sol - 14 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | 4 Str - 14 Str |
| Conductor Range AL Solid (Primary, run, main, line) | NA |

Voltage



Voltage Rating

600 V