

IMAGE
COMING
SOON

SKU: NRBR-10-12-P20

UPC: 0783669208528

Features & Benefits:

Description: ILSCON Ring Terminal, Conductor Range 10-12, 1/2in Bolt Size, Nylon Insulated, Yellow Color Code, Pack of 20

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Maximum Wire Insulation Diameter (IN)	0.252
Mounting Bolt/Stud Size (mm)	304.8

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	Nylon
Material	Copper

General

Bag Quantity	20
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366920852

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	20U0
UL / CULUS Specification	UL/cUL 486A/B Listed
UL File Number	E6207

Color

Color	Silver
Color Code	Yellow

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	Yes
Temperature Rating	105°C