



**SKU:** SPA-0

**UPC:** 0783669857023

**Features & Benefits:**

**Description:** Aluminum Splicer/Reducer, Dual Rated, Conductor Range 1/0-14, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Number of Ports / Wireways	2
Wire Orientation	Parallel

### Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	0.688
Height BX (IN)	2.25
Length (IN)	1.906
Weight (LB)	0.084
Weight BX (LB)	1.742
Width (IN)	0.625
Width BX (IN)	5

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1

Wire Binding Screw Size	3/8
Wire Binding Torque	10 - 14 AWG = 35

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366985702

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

## Environment and Temperature

Temperature Rating	90°C
--------------------	------

## Color

Color	Silver
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	1/0 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	1/0 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

## Voltage

Voltage Rating	35 kV
----------------	-------