



SKU: SPAR-350

UPC: 0783669857306

Features & Benefits:

Description: RocketSplice Insulated Aluminum Splicer/Reducer, Dual Rated, Conductor Range 350-10, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.78
Height BX (IN)	3.75
Height (mm)	45.212
Length (IN)	6.25
Length (mm)	158.75
Weight (LB)	0.712
Weight BX (LB)	2.531
Width (IN)	3.245
Width BX (IN)	6.5
Width (mm)	82.423

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	11/16
Wire Binding Torque	4 - 10 AWG = 100

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366985730

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Clear
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range AL Stranded (Secondary, tap, load)	350 kcmil - 10 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	350 kcmil - 10 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol

Voltage

Voltage Rating	600 V
----------------	-------