



SKU: SSK-350

UPC: 0676566789040

Features & Benefits:

Description: Watertight Underground Splice Kit, Dual Rated, Conductor Range 350-6, Includes (1) SS-350-Z Cover and (1) SPA-350 Splice

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Ports Tap	1

Dimensions

Drive Size Main	5/16
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	NA
Height (IN)	2.05
Height BX (IN)	18.75
Height (mm)	52.07
Length (IN)	9.746
Length (mm)	247.5484
Weight (LB)	0.432568142486611
Weight BX (LB)	27.5
Width (IN)	2.05
Width BX (IN)	14.625
Width (mm)	52.07

Additional Technical Specifications

Conductor Type	Stranded
Dielectric Strength	240 V/Mil

Material and Finish

Conductor Material	Copper
Insulation Material	EPDM
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Bolt and Screw Sizes

Wire Binding Screw Size

11/16-16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-569-2
UPC Code	67656678904

Environment and Temperature

Water tight	Yes
-------------	-----

Testing Standards

ANSI Specification	ANSI C119.4 Class A
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	350 kcmil - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	350 kcmil - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA