

IPEX INDUSTRIAL PRODUCT OVERVIEW

Xirtec® PVC – Xirtec® CPVC

1/2" – 24" (12mm – 600mm)

XIRTEC®: PVC Schedule 40
& 80 pipe and fittings systems.

XIRTEC®: CPVC Schedule 80
pipe and fittings systems
cell classification 24448 & 23447



Duraplus™ ABS Industrial

1/2" – 12" (12mm – 300mm)

Complete ABS pressure
pipe, valves and fitting systems.



PROCESS PIPING SYSTEMS



Enpure™

1/2" – 4" (12mm – 100mm)

High-purity polypropylene pipe, valves, and
fittings with a socket fusion joining system.



CORROSIVE WASTE SYSTEMS



Enfield™

1-1/2" – 12" (40mm – 300mm)

Electrofusion corrosive waste
system consists of Polypropylene
Schedule 40 & 80 IPS pipe
and fittings.



Labline®

1-1/2" – 4" (40mm – 100mm)

Mechanical joint corrosive
waste system in polypropylene
Schedule 40 and 80 IPS pipe
(flame-retardant and non-
flame-retardant) and fittings.



Plenumline™

1-1/2 – 4" (40mm – 100mm)

Flame-retardant PVDF mechanical joint
acid waste system made for return air
plenum high-temperature corrosive
chemical waste applications.



THERMOPLASTIC VALVES

Thermoplastic Valves

1/2" – 16" (12mm – 400mm)

IPEX offers a variety of manual & actuated
valves in PVC, CPVC, PP, PVDF and ABS.



Guardian™

Carrier: 1/2" – 12" (12mm – 300mm)
Containment: 2" – 18" (50mm – 450mm)

Vinyl double containment and leak detection system in tough industrial grade PVC and high temperature CPVC.



Encase™

1-1/2" – 12" (40mm – 300mm)

Polypropylene double containment system for corrosive waste drainage consisting of an electrofusion socket fitting with a heavy-gauge resistance wire.



PAL-AT Cable Leak Detection

A microprocessor based system for continuous leak detection.



Drain-Guard™

Carrier: 1-1/2" – 12" (40mm – 300mm)
Containment: 4" – 16" (100mm – 400mm)
(Larger sizes available upon request)

A complete double containment drainage system – enabling improved safety and reliability in Drain, Waste and Vent (DWV) applications.



DOUBLE CONTAINMENT SYSTEMS



CustomGuard™

Carrier: 1/2" – 20" (12mm – 500mm)
Containment: 2" – 26" (50mm – 660mm)

Custom designed and fabricated double containment systems for similar & dissimilar materials.



Clear-Guard™

1/2" – 8" (12mm – 200mm)

Fully pressure rated clear containment PVC system with Guardian's patented Centra-Lok fitting design.



Centra-Guard™

Patented electronic low point leak detection system for above ground and below grade piping systems.



Duratec® Airline

1/2" – 1" (12mm – 25mm)

Composite pipe and fittings for conveying compressed air and inert gases.



COMPRESSED AIR



Duraplus™ Airline

1/2" – 4" (12mm – 110mm)

A high-impact, ductile ABS pressurized piping system for conveying compressed air.

SPECIALTY PRODUCTS

Ventilation Duct

PVC 6" – 24" (150mm – 600mm)
CPVC 6" – 16" (150mm – 400mm)

Seamless PVC & CPVC ventilation duct systems for corrosive fume handling applications.



Well Casings

2" – 16" (50mm – 400mm)

PVC corrosion-resistant, maintenance-free casings for well-drop-pipe and submersible pumps.



Grooved PVC Pipe

2" – 24" (50mm – 600mm)

Schedule 40, 80, SDR 26 and SDR 21 factory-grooved PVC pipe.



Xirtec®, Enpure®, Duraplus®, Guardian™, Encase™, CustomGuard™, Centra-Guard™, Clear-Guard™, Drain-Guard™, Enfield™, Labline™, Plenumline™, and Duratec® are trademarks used under license.

Xirtec® CPVC piping systems are made with Corzan® CPVC compounds. Corzan® is a registered trademark of the Lubrizol Corporation.

IPEX USA LLC
Toll Free: (800) 463-9572
ipexna.com

