



## PIPE SLEEVING

### Specifications:

Furnish and install Water-Tite pipe sleeving to protect plastic and copper piping in concrete. Water-Tite pipe sleeving is most commonly used in concrete slab construction for pipes that are set into the concrete. Product shall be Water-Tite product code checked below as manufactured by IPS Corporation.

### FEATURES:

**Material:** Polyethylene

**Accommodates Pipe sizes:** 1/2", 3/4" and 1"

**Color-Coded:** Red = Hot and Blue = Cold

**Packaging:** Self-dispensing box



### DIRECTIONS:

1. Cut desired length of pipe sleeving
2. Insert piping into sleeve prior to pouring concrete slab
3. Red = Hot and Blue = Cold

### PRECAUTIONS:

Limit sun exposure, as prolonged exposure will eventually deteriorate polyethylene.

Read all directions and cautions prior to using this product

| ✓                                                                                               | Product Code # | Product Description                                    | Thickness | Width | Model # |
|-------------------------------------------------------------------------------------------------|----------------|--------------------------------------------------------|-----------|-------|---------|
|                                                                                                 | 83405          | Red for 1/2" - 1" Tubing (200' Roll)                   | 0.004"    | 2.25" | WTSR4   |
|                                                                                                 | 83407          | Blue for 1/2" - 1" Tubing (200' Roll)                  | 0.004"    | 2.25" | WTSB4   |
|                                                                                                 | 83400          | Red for 1/2" - 1" Tubing (200' Roll)                   | 0.006"    | 2.25" | WTSR    |
|                                                                                                 | 83404          | Blue for 1/2" - 1" Tubing (200' Roll)                  | 0.006"    | 2.25" | WTSB    |
|                                                                                                 | 83409          | Red for 1/2" - 1" Tubing (200' Roll)                   | 0.010"    | 2.25" | WTSR10  |
|                                                                                                 | 83410          | Blue for 1/2" - 1" Tubing (200' Roll)                  | 0.010"    | 2.25" | WTSB10  |
| <b>Ultra-Flex Heavy 25 mil. Pipe Sleeving is ideal for both CPVC and Copper Piping Systems.</b> |                |                                                        |           |       |         |
|                                                                                                 | 83416          | Red Ultra-Flex Heavy for 1/2" - 1" Tubing (100' Roll)  | 0.025"    | 2.18" | 83416   |
|                                                                                                 | 83417          | Blue Ultra-Flex Heavy for 1/2" - 1" Tubing (100' Roll) | 0.025"    | 2.18" | 83417   |
|                                                                                                 | 83418          | Red Ultra-Flex Heavy for 1/2" - 1" Tubing (50' Roll)   | 0.025"    | 2.18" | 83418   |
|                                                                                                 | 83419          | Blue Ultra-Flex Heavy for 1/2" - 1" Tubing (50' Roll)  | 0.025"    | 2.18" | 83419   |

**IPS**  
CORPORATION

500 Distribution Parkway, Collierville, TN 38017 ■ 800-888-8312 ■ Fax: 901-853-5008 ■ [www.ipscorp.com](http://www.ipscorp.com)