

Terminals & Connectors (K-Spec® Series)

PVC Insulated Spade/Fork Terminals (K-Spec® Series)



600V Rating, 75°C, Copper

22-18GA



Stud Size #6
561048 100 pk
561048D 500 pk



Stud Size #8
561049 100 pk
561049D 500 pk



Stud Size #10
561050 100 pk
561050D 500 pk

16-14GA



Stud Size #6
561061 100 pk
561061D 500 pk



Stud Size #8
561062 100 pk
561062D 500 pk



Stud Size #10
691063 9 pk
561063 100 pk
561063D 500 pk



Stud Size 1/4"
561064 100 pk
561064D 500 pk

12-10GA



Stud Size #6
561074 100 pk
561074D 500 pk



Stud Size #8
561075 100 pk
561075D 500 pk



Stud Size #10
691076 7 pk
561076 100 pk
561076D 500 pk



Stud Size 1/4"
561077 100 pk
561077D 500 pk

Fully Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)



300V Rating, Brass. Nylon (105°C). PVC (75°C)

22-18GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561354 100 pk
561354D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561353 100 pk
561353D 500 pk




Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561345 100 pk
561345D 500 pk

16-14GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561357 100 pk
561357D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561358 100 pk
561358D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561346 100 pk
561346D 500 pk

12-10GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561623 100 pk
561623D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561621 100 pk
561621D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561347 100 pk
561347D 500 pk

Crimp Tools can be found on pages 42-45