

K-SPEC® CABLE TIES

Standard Nylon Cable Ties (General Purpose)

- Material with Pure Nylon 6.6, UL 94V-2, Operation temp. -40°C~+85°C (-40°F ~+185°F)
- Suggested Installation temp. -10°C~+85°C (14°F~185°F)
- Products listed with:



RoHS PAHs Reach

**PLENUM
RATING
AH-2**



A

	Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
M	E4180C	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4180M	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E4189C	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4189M	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E6180C	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6180M	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E6189C	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6189M	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E8180C	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8180M	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E8189C	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8189M	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E14180C	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100
	E14180M	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000
	E14189C	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100
	E14189M	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000
I	E5400C	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5400M	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E5409C	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5409M	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E8400C	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8400M	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E8409C	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8409M	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E11400C	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11400M	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E11409C	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11409M	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E14400C	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100
	E14400M	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000
	E14409C	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100
	E14409M	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000

**NEW
NEW
NEW
NEW**

K-Spec® Part No. Instructions:

E20175

└─── Pack Qty Code
└─── Colour Code

Pack Qty	Code
50	L
100	C
500	D
1000	M

Colour	Code	Colour	Code
Natural	9	Blue*	6
White*	WH	Purple*	7
UVB Resistant Black	0	Gray*	8
Brown*	1	FL. Orange*	16
Red*	2	FL. Yellow*	17
Orange*	3	FL. Green*	18
Yellow*	4	FL. Blue*	20
Green*	5		

* 100,000 Piece Minimum Order for Coloured Ties