

KNIPEX Quality – Made in Germany



KNIPEX CoBolt® S Compact Bolt Cutters

6 1/4" (160 mm) Pocket-sized length

Now available with a Recess



Blade recess for easier cutting of larger materials

Strongest cutters of their length due to lever action design

Gripping surface for pulling wire

KNIPEX CoBolt® S
Compact Bolt Cutters

71


- ▶ Extremely high cutting performance in a convenient length of 6 1/4" (160 mm)
 - ▶ Small, slim head for better access to confined areas
 - ▶ Heavy-duty cutting edge with recess slices through the hardest round materials in only one cutting action
- > Compact and powerful: cuts bolts, nails, rivets etc. up to a diameter of 13/64" (5.3 mm)
 - > Heavy duty, induction hardened edges for cutting thin, hard wire, screws and springs. Cutting edge hardness (approx. 64 HRC)
 - > Less physical effort required due to efficient lever action mechanism
 - > No slipping of the material being cut due to lasered cutting edge
 - > Gripping surface below the joint for gripping and pulling wires with a diameter from 3/64" (1.0 mm)
 - > Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened



71 01 160



71 31 160



NEW

With recess in the cutting edge



Powerful cutting even at the tips of the blades



With its slim head, the KNIPEX CoBolt® cuts where other bolt cutters will not even come close

Part Number	↔		Handles	Cutting Blades	Cutting Capacities							
	inch	mm			Ø inch	Ø mm	Ø inch	Ø mm	Ø inch	Ø mm	Ø inch	Ø mm
71 01 160	6 1/4	160	plastic coated	straight	13/64	5.3	11/64	4.4	1/8	3.2	1/8	3.0
71 01 160 SBA	6 1/4	160	plastic coated	straight	13/64	5.3	11/64	4.4	1/8	3.2	1/8	3.0
71 31 160	6 1/4	160	plastic coated	recess	13/64	5.3	3/16	4.8	9/64	3.6	1/8	3.3
71 31 160 SBA	6 1/4	160	plastic coated	recess	13/64	5.3	3/16	4.8	9/64	3.6	1/8	3.3

SBA signifies hang-up packaging (POP Carded)

KTLP20033