The compact bolt cutters from KNIPEX are now available with longer handles for one and two-handed operation.

Up to a 40-fold increase of manual force

For powerful cutting of larger diameters as well as very hard materials Two-handed operation for maximum cutting force

- > 60% less effort required compared to high leverage diagonal cutters of the same size
- > 40-fold increase of manual force due to special joint design
- > gripping surface below the joint for gripping and pulling wires with a diameter from 3/64" (1 mm)
- > induction hardened precision blades: cutting edge hardness (approx. 64 HRC)
- > chrome vanadium heavy-duty steel; forged, multi stage oil-hardened

71 01 250

Straight blades

71 31 250

Blades with notch for easier cutting of larger diameters due to a better leverage close to the fulcrum











						Cutting capacities			
Product Number	Packaging	←→ Inch mm		Pliers	Handles	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	∆¹∆ Ibs
71 01 250	Х	10 250	Þ4	black atramentized	plastic coated	7/32 5.6	5/32 4.0	5/32 3.8	1.03
71 31 250	Х	10 250	M	black atramentized	plastic coated	1/4 6.0	11/64 4.3	11/64 4.2	1.03

KNIPEX CoBolt® "Fencing" Compact Bolt Cutter

71

- > the CoBolt $^{\! \otimes}$ with reduced cutting edge hardness to allow more pressure on the sides of the cutting edges (e.g. for making fences)
- > with precision cutting edges for soft and hard wire
- > cutting capacity: max. Ø 5/32" for hard wire (up to 1900 n/mm² / 48 HRC)
- > cuts material like bolts, nails, rivets, etc. up to 13/64" (5.2 mm) dia.
- > exceptional cutting performance with minimum effort because of new lever action design
- > induction hardened cutting edges (approx. 62 HRC)
- > chrome vanadium heavy-duty steel; forged, oil-hardened

71 31 200 R

The recess in the blade allows easier cutting of thicker wires, e.g. for false ceilings





						Cutting capacities			
Product Number	Packaging	←→ Inch mm		Pliers	Handles	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	∆¹∆ Ibs
71 01 200 R	X	8 200	Þ 4	black atramentized	plastic coated	15/64 6.0	13/64 5.2	5/32 4.0	0.74
71 31 200 R	X	8 200	M	black atramentized	plastic coated	15/64 6.0	13/64 5.2	5/32 4.0	0.74