Product information

95 26 165

Cable Shears

With opening spring

IEC 60900 DIN EN 60900

- For cutting copper and aluminium single conductors as well as multiple stranded cables
- Clean and smooth cut without crushing and deformation
- Not suitable for steel wire and hard drawn copper conductors
- Precision-ground, hardened blades
- Easy cutting with one-hand operation
- With guard
- Adjustable bolted joint, self-retaining screw
- Internal opening spring, protected and captive
- High-grade special tool steel, forged, oil-hardened

1000 V

General	
Article No.	95 26 165
EAN	4003773069980
Shears	chrome-plated
Handles	insulated with multi-component grips, VDE-tested
Weight	275 g
Dimensions	165 x 63 x 26 mm
Standard	DIN EN 60900 IEC 60900
Reach-konform	no
RohS	no

Technical details	
Cutting capacity copper cable, multiple-stranded	50 mm²
Cutting capacity copper cable, multiple-stranded	Ø 15 mm
AWG	1 / 0
VDE tested	yes

Classification	
eCl@ss 5.1.4	21040601
ETIM 5.0	EC000142
ETIM 6.0	EC000142
proficl@ss 6.0	EAD256c001
UNSPSC 13.1	23241616

technical change and errors excepted

Cut performed with a Cable Shear: easy, clean cut without any deformation of the cable

95 26 165: Catch locks shears to the opening spring inside