

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and wire ropes
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > one-hand operation using ratchet principle
- > minimal handforce required due to very high transmission ratio
- > two-stage ratchet drive for easy cutting
- > simple handling as a result of lightweight and compact design – can be used even in confined areas
- > pinch guard prevents operators' fingers being pinched
- > high-grade special tool steel; forged, oil-hardened



95 31 250 SBA



95 31 280: Large cutting capacity:
max. 2" (52 mm) dia. / 380 mm²



Ratchet principle and two-stage ratchet drive
for easier cutting



95 31 280 SBA



95 31 250/280: Fixed handle with support area as an aid to position the pliers when cutting



95 36 250 SBA



Product Number	Packaging	↔ Inch mm	Icons	Tool	Handles	Cutting capacities			⚖ lbs
						⊕ Ø Inch Ø mm	⊕ mm ²	MCM	
95 31 250 SBA	X	10 250	⊕ MM ⊕	black lacquered	multi-component grips	1 1/4 32	240	500	1.49
95 31 280 SBA	X	11 280	⊕ MM ⊕	black lacquered	multi-component grips	2 3/64 52	380	750	1.70
95 36 250 SBA	X	10 250	⚡ 1000 V ⊕ ⊕ MM ⊕	black lacquered	insulated, multi-component grips, VDE-tested	1 1/4 32	240	500	1.24
95 36 280 SBA	X	11 280	⚡ 1000 V ⊕ ⊕ MM ⊕	black lacquered	insulated, multi-component grips, VDE-tested	2 3/64 52	380	750	1.64
95 39 250	Movable spare blade for 95 31 250 / 95 36 250								
95 39 280	Movable spare blade for 95 31 280 / 95 36 280								