

# Electrical Accessories and Decorative Devices

## INDEX

<b>Residential Grade Electrical Accessories and Decorative Devices</b>	
Taps and Adapters	U2
Night Lights	U3
Guide Lights	U4
Fluorescent Utility Lights	U4
Child Protection Devices	U4
Accessories	U4
Wallplates	U5





# ADAPTERS

## Residential Grade Devices

LEVITON OFFERS A VARIETY OF ELECTRICAL ACCESSORIES FOR RESIDENTIAL USE, INCLUDING TAPS, SURFACE OUTLETS, ADAPTERS, NIGHT LIGHTS AND SAFETY ITEMS USED FOR CHILD PROTECTION.

### Switch Tap

#### 13 AMP 125V 2-Pole 2-Wire Non-Grounding

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Plug-In Switch Tap	1469	I, W	1-15R



1469-W



69-W



607-W



698-W



1403-W

### Plug-In Outlet Adapters

#### 15 AMP 125V 2-Pole 2-Wire Non-Grounding

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Single-to-Triple 3 round or flat plugs accepted	63	I, W	1-15R
Single-to-Triple Right Angle, 3 round or flat plugs accepted★	65	I, W	
Single-to-Triple, Swivel, 3 flat plugs accepted	69	I, W	
Cube Tap, Vinyl, 3 round or flat plugs accepted	531	I, W	

#### 15 AMP 125V 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
3-Wire, Grounding Duplex-to-Six, 6 small or 4 large plugs accepted	49686	I, W	5-15R
3-Wire, Grounding Single-to-Triple, 3 straight or angle plugs acceptedH	697	I, W	
3-Wire, Grounding Single-to-Triple, Vinyl, 3 straight or angle plugs accepted	699	Orange only	
3-Wire, Grounding Single-to-Triple, 3 straight plugs accepted	694	Orange, Green	
Triple Cube Adapter	692	I, W	

#### 15 AMP 125V 2-Pole 2-Wire to 2-Pole 3-Wire Grounding

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Adapter, 2-Wire to Grounding, 1 straight or 1 angle plug accepted★	274	Gray	5-15R
2-Wire to Grounding, 3 straight plugs accepted★	698	I, W	

Note: All Leviton #274 and #698 adapters use the outlet wallplate screws for grounding.

### Medium Base Lampholder Outlet Adapters

#### 660 WATT 125V 2-Pole 2-Wire

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Outlet-to-Lampholder★	61	I, W	1-15R
Lampholder-to-Outlet	125	I, W	
Keyless Lampholder and 2 Outlets	1403	I, W, E	
Single Lampholder-to-Twin Lampholder (660W-250V)	128	I	

#### 660 WATT 125V Max. Total 2-Pole 2-Wire

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Pull Chain Lampholder and 2 Outlets. Pull chain controls lamp socket ONLY. Outlet continuously live.	1406	I, W, E	1-15R

CSA Certified except where indicated by★

#### SPECIFICATIONS AND FEATURES

##### Plug-In Switch

- Provides ON/OFF switching at outlet location

##### Plug-In Outlet Adapters

- Convenient expansion of outlet capacity

#### TESTING AND CODE COMPLIANCE

- UL Listed (File #E13393 – Cat. No. 125; File #E13394 – Cat. Nos. 1469, 49686, 692, 694, 697, 698, 274, 128, 1403 and 1406; File #E-13399 – Cat. Nos. 63, 65, 69, 531)
- CSA Certified (File #LR-406 – Cat. No. 125; File #LR-1523 – Cat. No. 63; File #LR-2780 – Cat. No. 128; File #LR-61476 – Cat. Nos. 65, 69, 531 and 1469; File #LR-91345 – Cat. No. 49686)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

#### \*COLOR

Basic Cat. No. denotes Brown device. For other color selections, add suffix to catalog number as follows: Ivory (-I), White (-W), Almond (-A) and Black (-E).



Night Lights

**ON/OFF Night Light 4 WATT 125V**

DESCRIPTION	CAT.NO	COLOR*
ON/OFF switching with sleek, contemporary styling	48566	I, W

**Automatic Light Directing LED Night Light .25W 120V**

DESCRIPTION	CAT.NO	COLOR
Removable shade slides up and down to direct light	48585	W

**Automatic Rotating Spotlight 120V**

DESCRIPTION	CAT.NO	COLOR
Automatic ON/OFF with 360° rotating head directs light and varies intensity (2.4W)	49566	W
LED Automatic ON/OFF with 360° rotating head directs light and varies intensity (.5W)	49566-LED	W

**Automatic Night Light 4 WATT 125V**

DESCRIPTION	CAT.NO	COLOR* (Night Light Base)
Automatic ON/OFF sensor with sleek, contemporary styling	48568	I, W

**Automatic LED Night Light .25W 120V**

DESCRIPTION	CAT.NO	COLOR
Automatic ON/OFF with light-reflecting, crystal-faceted shade	48580	BLU (Blue) GRN (Green) WHT (White)

**Automatic Sound-Activated Night Light 125V**

DESCRIPTION	CAT.NO	COLOR
Sound-Activated with adjustable sensitivity (4W)	51012	W
LED Sound-Activated with adjustable sensitivity (.5W)	51012-LED	W

**Decorative Shade LED Night Lights .5W 120V**

DESCRIPTION	CAT.NO	COLOR
<b>49563 Series</b> —Consult your Leviton representative for available shade designs	49563	W



**Leviton's Energy Smart Living Program**

Leviton offers a broad range of energy-efficient lighting devices for homes and businesses. From dimmers, timers and motion sensors to night-lights and more, Leviton has the electrical products you need to save energy and conserve resources. Look for the Energy Smart Living logo, your assurance of an environmentally friendly lighting product. For more information, visit our website at [www.leviton.com](http://www.leviton.com).



48566-W



48580-WHT



51012



49563-SWL



49563-PLM

**SPECIFICATIONS AND FEATURES**

**Automatic Night Lights**

- Turn ON automatically at dusk and OFF automatically at dawn, by sound or by movement depending on model
- Long-life 4 watt bulb or LED included

**TESTING AND CODE COMPLIANCE**

- UL Listed (File #E-39445 – Cat. Nos. 16509, 48566, 48581, 49563, 49566 and 51012; File #E-121173 – Cat. No. 48568)
- CSA Certified (File #LR-1863 – Cat. Nos. 48566, 48568 and 49566)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

**\*COLOR**

Add suffix to catalog number as follows for color selections: Ivory (-I), White (-W).



Residential Grade Devices

Electrical Accessories and Decorative Devices



49568



6511-6



6516



12540

**Guide Lights**

DESCRIPTION	CAT.NO	COLOR
Button-Style Neon Guide Light .25 Watt 120V AC	49567	W
LED Guide Light with clear shade .5 Watt 120V AC	49568	W (Amber LED) BLU (Blue LED)

**Cool Glow Night Light**

DESCRIPTION	CAT.NO	COLOR
Electro-Luminescent Guide Light 1 pack .03W 115V	16509-1PK	W
Electro-Luminescent Guide Light 2 pack .03W 115V	16509-2PK	W

**Utility Lights**

DESCRIPTION	CAT.NO	COLOR
6" Battery-Operated Fluorescent Light—With 4W replaceable bulb. Requires 4 AA batteries (not included). 6V DC Jack for use with AC/DC adapter (Sold separately)	6511-6	(White base only)
6" Battery-Operated Closet Utility Light with ON/OFF switch (2 pack)—Requires 3 AA batteries (not included)	6516-2PK	(White base only)

**Child Protection Devices**

**Outlet Cover Night Light .25 WATT**

DESCRIPTION	CAT.NO	COLOR
Cool neon light on top outlet, cover on bottom outlet	48500	(White base only)

**Outlet Caps**

DESCRIPTION	CAT.NO	COLOR
Outlet Caps—12 Pack	12777	White only

**Tamper Resistant Receptacles 15 AMP 125V 2-Pole 3-Wire Grounding**

DESCRIPTION	CAT. NO.	COLOR	NEMA CONFIG.
Tamper Resistant Receptacle	5321	I, W	5-15R

**Electrical Accessories**

DESCRIPTION	CAT.NO	COLOR
Insulated Staples— <sup>5</sup> / <sub>8</sub> " long, for use with 18/2 or smaller cord (40 Pieces)	12533	White
Plastic Staples—for <sup>1</sup> / <sub>2</sub> " 14/2 & 12/2 NM Cable (50 Pieces)	12536	White
Wiring Fasteners—Includes <sup>1</sup> / <sub>2</sub> " Plastic Staples, Coax Cable Fasteners and <sup>1</sup> / <sub>2</sub> " X 1" Metal Staples (47 Mixed Pieces)	12537	White/Black/ Metal Mix
NM Cable Fittings— <sup>3</sup> / <sub>8</sub> " dia. for 14/2, 14/3 & 12/3 NM Cable (4 Pack)	12538	—
8" Cable Ties—Holds wires, cables, bundles and hoses; comes in assorted lengths and colors	12540	White, BL (Black) NE (Neon)

**SPECIFICATIONS AND FEATURES**

- Guide Lights**
  - Energy-efficient with soft, comforting light
  - Compact Neon model keeps second outlet free
  - No bulb to replace in LED models
- Utility Lights**
  - Battery operation adds light without wiring anywhere extra light is needed
  - Includes adhesives for easy, anywhere mounting
- Outlet Caps**
  - Insert into unused outlets to serve as a barrier
  - Can be easily removed by adults when needed for lights and appliances
- Tamper Resistant Receptacle**
  - Exclusive design helps prevent insertion of anything but a properly rated plug
  - Floating shutters behind outlet faces block clear access to energized contacts

**TESTING AND CODE COMPLIANCE**

- UL Listed (File #E-84313 – Cat. Nos. 48500; File #E-7416 – Cat. No. 12777; File #E-13399 – Cat. No. 5321)
- CSA Certified (File #LR-64317 – Cat. No. 48500; File #LR-406 – Cat. No. 5321)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

**\*COLOR**

Add suffix to catalog number as follows for color selections: Ivory (-I), White (-W), Black (-E).



### The Finishing Touch® Wallplates

Available in warm wood tones and decorative metals, The Finishing Touch® wallplates are perfect for decorating, redecorating or adding an accent to any room. These wallplates feature elegant and stylish finishes with an oversize silhouette for complete coverage.

#### Decorative Wood — Straight Edge

DESCRIPTION	CAT. NO.	COLOR
1-GANG, 1-Toggle	89201-OAK	Oak
	89201-CHR	Cherry
	89201-UNF	Unfinished
	89201-WWP	Whitewash
2-GANG, 2-Toggles	89209-OAK	Oak
	89209-CHR	Cherry
	89209-UNF	Unfinished
	89209-WWP	Whitewash
1-GANG, 1-Duplex	89203-OAK	Oak
	89203-CHR	Cherry
	89203-UNF	Unfinished
	89203-WWP	Whitewash

#### Wood — Scalloped Edge

DESCRIPTION	CAT. NO.	COLOR
1-GANG, 1-Toggle	89201-CVP	Pine
2-GANG, 2 Toggle	89203-CVP	Pine
1-GANG, 1 Duplex	89209-CVP	Pine

#### Wood — Beveled Edge

DESCRIPTION	CAT. NO.	COLOR
1-GANG, 1-Toggle	89201-POK	Oak
1-GANG, 1-Duplex	89203-POK	Oak

#### Decorative Metal

DESCRIPTION	CAT. NO.	COLOR
1-GANG, 1-Toggle	89301-ATB	Antique Brass
	89301-SSS	Satin Chrome
	89601-STB	Stepped Brass
2-GANG, 2-Toggles	89309-ATB	Antique Brass
	89309-SSS	Satin Chrome
	89609-STB	Stepped Brass
1-GANG, 1-Duplex	89303-ATB	Antique Brass
	89303-SSS	Satin Chrome
	89603-STB	Stepped Brass

For the full offering of Decorative Wallplates contact your Leviton representative.

#### SPECIFICATIONS AND FEATURES

##### Decorative Wood and Metal Wallplates

- Genuine wood available in Oak, Cherry, Whitewash and Unfinished
- Metal available in Antique Brass, Satin Chrome White Vinyl and Stepped Brass
- Sturdy impact-resistant construction for long-lasting performance
- Modern design with oversized silhouette for complete coverage
- Clean attractive appearance
- Smooth surface is easy to keep clean
- Mounting screws included—Metal plates feature matching-color screws



89201-OAK



89209-CHR



89203-CVP



89309-SSS



89601-STB

# TABLE OF CONTENTS with Quick Reference Index

The L-101 Leviton Wiring Device Catalog is designed to help you find the device you're seeking in the quickest and easiest way possible. Most product sections are divided into three distinct categories in the following sequence—Industrial Grade, Commercial Grade and Residential Grade—and grouped according to amperage and voltage, lowest to highest. For example, if you need to order 15 Amp, 125 Volt Industrial Grade straight-blade duplex receptacles, begin your search with the main Table of Contents at the front of the book. Here you'll see that all straight blade receptacles are listed in Section G. Turn to Section G for a more detailed Table of Contents on the first page. Each section page contains product descriptions, ratings and catalog numbers. There are also helpful highlights including Specifications and Features, Testing and Code Compliance, Color listing, Material Characteristics and dimensioned color product photos. Any product page in the L-101 Catalog can be clearly copied or faxed to customers and prospects for use as a specifier sheet or as part of a presentation.

The Quick Reference Guide follows the main Table of Contents to help you pinpoint and locate specific products. Technical Section V provides general product and test data, industry standards, NEMA configuration charts, a glossary of wiring device terms, ANSI architectural symbols and other related information. Specific catalog numbers are listed in the exhaustive index at the back of the catalog.

## 15 AMP 125 and 250V • 20 AMP 125 and 250V

### Industrial Grade Straight Blade Receptacles

**Back and Side Wired** (Basic Cat. No. Denotes Brown Device\*)

DESCRIPTION	CAT. NO./COLOR 15A/125V	CAT. NO./COLOR 15A/250V	CAT. NO./COLOR 20A/125V	CAT. NO./COLOR 20A/250V
LEVSPEC® Duplex Receptacle, Brass Strap	5262 I, W, GY, R, E	5662 I	5362 I, W, GY, R, E	5462 I, GY
Single Receptacle	5261 I, W, GY	5661 I	5361 I, W, A, T, GY	5461 I, A, T, GY
Narrow Body Duplex Receptacle	5252 I, W, A, T, GY, R, E, BU		5352 I, W, A, T, GY, R,	

**For complete wallplate selection, see Section E.**

**SPECIFICATIONS AND FEATURES**

**Back & Side Wired Duplex**

- Impact-resistant thermoplastic nylon cover and body
- Smooth face does not collect dirt
- Four corner latches securely fasten face
- Single-piece brass mounting strap on LEVSPEC devices, multi-piece steel strap on other devices
- Large, triple-wipe, brass "T" contacts for superior contact and conductivity
- Back and side-wiring options
- Brass terminal screws to reduce conductor oxidation
- Break-off tabs for easy two-circuit conversion
- Apron barrier to prevent accidental contact between terminal screw heads and metal box
- Exclusive V-shaped, serrated back-wiring clips for superior contact and conductivity

**TESTING AND CODE COMPLIANCE**

- UL Listed 498 (UL File #13399); UL Federal Specification WC-596

- Meets NEMA WD-1 & 6, and ANSI standards
- Backed by a Limited 10-Year Warranty
- SPECCLASS devices backed by a Limited 2-Year Warranty

**\*COLOR**

Basic Cat. Nos. shown above denote Brown device, except for Isolated Ground (-IG) devices. Basic Cat. No. denotes Orange. Isolated Ground Receptacle is distinguished by an orange triangle on its face. For other color selections, add suffix to the catalog number as follows: Ivory (-I), White (-W), Brown (For IG devices only, add -B), Almond (-A), Light Almond (-T), Gray (-G or -GY), Black (-E), Red (-R) and Blue (-BU; for IG devices only, add -BIG)

**MATERIAL CHARACTERISTICS**

Environmental: Flammability, Rated V2  
Operating Temperature: From -40° C (without impact) to 60° C maximum continuous

<b>A</b> RATING	<b>E</b> CATALOG NUMBER	<b>I</b> SPECIFICATIONS & FEATURES
<b>B</b> Choose GRADE, if appropriate	<b>F</b> DESCRIPTION	<b>J</b> TESTING AND CODE COMPLIANCE
<b>C</b> DIMENSIONED PHOTOGRAPH	<b>G</b> Check for NEMA CONFIGURATION	<b>K</b> COLOR LISTING
<b>D</b> WIRING/CERTIFICATIONS	<b>H</b> WALLPLATE REFERENCE, if appropriate	<b>L</b> MATERIAL CHARACTERISTICS

U  
6