

18202-LB

Double-Pole Tamper-Resistant Toggle Switch, Heavy-Duty Industrial Specification Grade, Canadian, 15 Amp, 347 Volt AC, Back or Side Wire, Brown



UPC Code : 07847735846

Country Of Origin : Please Contact Customer Service.

Technical Information

Standards and Certifications

ANSI : C-73

Amperage : 15 A

CSA C22.2 No. 111 : File #152105

Device Type : Tamper-Resistant Toggle Switch

Feature 4 : Canadian

Function : Double-Pole

Grade : Heavy-Duty Industrial Specification Grade

Standards and Certifications : UL/CSA

Termination : Back or Side Wire

UL Fed Spec WS896E : File #E7458

UL Standard : UL20

Voltage : 347 VAC

Warranty : 10-Year Limited

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40°C to 65°C

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Torque Range : 12-14 inch pounds

Material Specifications

Actuator Material : Thermoplastic

Base Material : Thermoplastic

Body Material : Thermoplastic

Contact Material : Silver Alloy

Cover Material : Thermoplastic

Dielectric Voltage : Withstands 1500V for 1 minute

Endurance : 50,000 cycles minimum

Overload UL20 Test : 100 cycles of OL at 4.8 times rated current

Strap Material : Steel

Temperature Rise : Maximum 30 degrees C rise

Terminal Screws : Brass 8-32

Toggle : Polycarbonate

Product Features

Amperage : 15 A

Base Material : Thermoplastic

Contact Material : Silver Alloy

Cover Material : Thermoplastic

Device Type : Tamper-Resistant Toggle Switch

Feature 4 : Canadian

Function : Double-Pole

Grade : Heavy-Duty Industrial Specification Grade

Strap Material : Steel

Terminal Screws : Brass 8-32

Termination : Back or Side Wire

Toggle : Polycarbonate

Voltage : 347 VAC

Mechanical Specifications

ANSI : C-73

CSA C22.2 No. 111 : File #152105

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Torque Range : 12-14 inch pounds

UL Fed Spec WS896E : File #E7458

UL Standard : UL20

Warranty : 10-Year Limited

Electrical Specifications

Dielectric Voltage : Withstands 1500V for 1 minute

Endurance : 50,000 cycles minimum

Overload UL20 Test : 100 cycles of OL at 4.8 times rated current

Temperature Rise : Maximum 30 degrees C rise

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:		
JOB NUMBER:			

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

