

# **LEDBAR**

LED Fluorobar Cabinet, Cove & Display

Job Information		
Project Name		Туре
Location		
Quantity		Date
Contact/Phone		
Notes		

## **Features**

## Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body on/off switch is provided for individual control (except 9" models).

#### LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 50 / 60Hz.

#### Light Output

This accent light is available in 2700 K, 3000 K, 4000 K or 5000 K colour temperatures, providing up to 1800 lumens, 111 lumens/watt.

#### Dimming

Fixture is 100~0% dimmable with industry standard TRIAC, ELV and Incandescent dimmers.

#### **LED Characteristics**

Powered by LED integrated strip that maintains uniform intensity with 70% lumens at 36.000 hours with a rated life

Lumens



#### **Beam Spread**

The fixture lens provides for 160° beam spread.

#### Linking

Complete with a joiner, these no shadow linking fixtures can be linked up to 10 units in a single run.

## **Mounting Kit**

Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.

## **Operating Temperature**

-10°C~40°C (14°F~104°F).

250

400

400


400

SPECIFICATION		
Approved Location	Dry	
Beam Angle	160°	
ССТ	2700 K / 3000 K /	
661	4000 K / 5000 K	
Certification	cULus	
Connection Type	3-Wire	
CRI	90+/80+	
Dimming	Yes	
Dimming Technology	TRIAC / ELV /	
Dimming Technology	Incandescent	
Lumens	Up to 1800	
Lumens per watt	Up to 111	
Max. Operating Temp.	40°C	
Min. Start Temp.	-10°C	
Lumen Maintenance	70% @ 36,000 hrs	
Power Factor	>0.9	
Rated Life	25,000 hrs	
THD	<15	
Voltage	120V	
Warranty	3 Years	
Wattage	Up to 22	



## Description

This LED Fluorobar light is a linear light with an integrated LED strip. Available with various lengths to meet any installation application.



775

775

850

1175

1000

1500

1200

1800


1800

1800



# **Ordering Guide**

## LEDBAR



58:58" 22W

**Fixture Length** 

3000 K

4000 K

5000 K



**Colour Temperature** 

30K: 3000 K 40K : 4000 K

150

250

250

#### Notes:

<sup>1</sup> Title 24 is currently only available with 2700 K CCT. <sup>2</sup> 2700 K LEDBAR34 not energy star certified.

Accessories are sold separately. For additional options consult your Liteline representative.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

**Liteline Corporation** Telephone Copyright © 2018 416.996.1856 All rights reserved. 1.866.730.7704

Fax 905.709.5255 1.888.738.9736



## **Accessories (Power feed required)**

#### **Power Cord**

ALFT6000-WH-3 6' Flexible 3-wire power cord for FluoroBar series.

# FBT6124-BL-WH-3

24" Flexible 3-wire power cord with bare



ALFT6000S-WH-3 6' Flexible 3-wire power cord with on/off switch, for FluoroBar series.



ALFT6016-WH-3 16" Flexible 3-wire power cord for FluoroBar series.

leads.



## ALFT60901-WH-3

6' Flexible 3-wire power cord with  $90^\circ$ connector (top connection).

## ALFT60904-WH-3

6' Flexible 3-wire power cord with 90° connector (right connection).



ALFT60902-WH-3 6' Flexible 3-wire power cord with 90° connector (left connection).



<u>6.</u>...

-

ALFT60903-WH-3 6' Flexible 3-wire power cord with 90° connector (bottom connection).

# Hardwire Box



ALFT6300-WH Hardwire box for FluoroBar series, with on/off switch.

## Flexible Cord with 90° Connectors

- ALFT90-WH-3 6" Flexible 3-wire cord with 90° connectors (top connection).
- ALFT903-WH-3 6" Flexible 3-wire cord with 90° connectors (right connection).

## **Flexible Connectors**

1:

1

FBT6106-WH-3 6" Flexible 3-wire connector.



FBT6100-WH-3 12" Flexible 3-wire connector.

6" Flexible 3-wire cord with 90°

connectors (left connection).

ALFT901-WH-3

6" Flexible 3-wire cord with 90° connectors (bottom connection).

ALFT902-WH-3

#### FBT6124-WH-3 24" Flexible 3-wire connector.

## FBT6136-WH-3

36" Flexible 3-wire connector

## Clips



LEDBAR-MAGCLIP-3 Magnetic mounting clips for LEDBAR, 3-pack.