



LED-DVR-24V-60W

60W Class 2 LED Plug-In Driver, 24V

Cabinet, Cove & Display

| Job Information | | |
|-----------------|--|------|
| Project Name | | Туре |
| Location | | |
| Quantity | | Date |
| Contact/Phone | | |
| Notes | | |

Features

Electrical Performance

- Max load 60W (output)
- Open and Short circut protection
- Over voltage protection
- Current protection: 3.8A
- 24V DC output

AC Input Details

- AC input voltage range: 100-240V
- AC input current: 1.5A
- Input frequency range: 50/60Hz
- Power factor: ≥0.5
- No load power consumption: 0.5W
- Leakage current: <0.25mA
- Effi ciency: 84%
- Input cable: 1.5m

DC Output Details

- DC current: 2.5A
- Working effi ciency:
- * 80% @ 115V AĆ
- * 80% @ 230V AC
- Output cable: 1.5m

Environmental Requirements

- Working temperature: 0-40°C
- Storage humidity: 5-90% RH

Linkage

- The LED driver is equipped with a DC 2.1 jack and 24 AWG SPT cord on the output side for linking 24V LED products.
- When used with outdoor LED fi xtures, the driver must be installed indoors or enclosed in a watertight box.

Compatibility

Compatible with all DazzLED 24 volt LED fixtures. The overall wattage load of the product should not exceed 80% of 60W (48W). Overloading the LED power supply may affect the longevity, overall performance and void the warranty.

| SPECIFICATION | | |
|-----------------------------|----------------|--|
| Amperage2.5A | | |
| ApplicationUndercabir | | |
| Approved LocationDry | | |
| Certifi cationcULus | | |
| Classifi cationClass II | | |
| ColourBK | | |
| DimmingNo | | |
| Link ConnectorDC 2.1 | | |
| Max. Op. Temp.40°C (| 104°F) | |
| Min. Start Temp.0°C (\$2°F) | | |
| Power Factor | ≥0.5 | |
| Power Supply TypeCo | nstant Voltage | |
| Plug-in Voltage100-24 | OV AC | |
| Primary Voltage24V DO | C | |
| Warranty3 Years | | |
| Wattage60W | | |

1-3/8"

35mm

(•°•)


2-1/16"

52mm



Description

LED-DVR-24V-60W is a class 2, constant voltage, 24V, 60W (max.) LED plug-in driver (power supply) for use with 24V LED fi xtures. Driver is suitable for dry location use only.





Notes: Accessories should be ordered separately. For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifi cations are subject to change without notice.

Ordering Guide



LED-DVR-24V-60W

60W class 2 LED plug-in driver, 24V.



www.liteline.com



