

CDS LED

Contractor Dual Strip Light

Strip Lighting, Designed to be as Easy as 1-2-3.

From order to installation, using the CDS Contractor Dual Strip is as easy as 1-2-3. Designed and priced to replace traditional fluorescent fixtures, the CDS LED strip light delivers the lumens you need while saving up to 34% in energy over traditional fluorescent fixtures. The CDS is a light-duty strip for basic applications and is designed to be the distributors' and contractors' best friend by saving them time and effort from the start of the project until it's complete.

1. Easy to Replace Fluorescent

The CDS LED strip light is designed to be a one-for-one replacement of 2- or 4-lamp fluorescent strip lights with up to 9,000 lumens for your commercial, storage, warehouse, office and display applications. The CDS is engineered for value, and the cost to convert from fluorescent to LED has never been better.

2. Easy to Order

Simply choose from four main options: length, voltage, color temperature and CRI.

3. Easy to Install

The CDS can be surface or suspension mounted. An alignment bracket comes with each fixture to allow for the fixtures to be mounted in a straight, continuous row. Also, the 8' option allows you to complete your job with half the luminaires and half the wiring connections versus using only 4' fixtures, meaning you can finish the job faster than ever before.




Quick Facts:

- 2,200 (2'), 4,200 (4') or 9,000 (8') lumens
- Up to 120 LPW
- Available in 2', 4' and 8' lengths
- Available in 3500K, 4000K & 5000K CCT
- Continuous-row mounting
- End-to-end illumination
- No Pixilation
- 35°C Ambient Rating

The Most Complete LED Strip Lighting Portfolio

The LED strip light portfolio from Lithonia Lighting® provides superior performance for a wide-variety of applications. Advanced LED technology provides longer life compared to fluorescent strip lights resulting in reduced maintenance costs and improved ROI.

	Contractor			Architectural	
	CDS	ZL1N	ZL1D	ZL1F	PTNSL
					
Intended Use	Entry Level, Contractor-Grade Strip	Designed for Maximum Efficacy	Optimized for Uplight	Low Glare	Aisle Distribution
Lens	Lamp-Like-Round Lenses	Narrow Flat Lens	Drop Lens	Wide Diffused Flat Lens	Flat Lens Optimized for Aisle Distributions
Lumen Packages	2,200, 4,200 & 9,000 Lumens	1,500-14,000 Lumens	1,500-14,000 Lumens	1,500-12,000 Lumens	3,500 & 7,300 Lumens
4', 8' Lengths	■	■	■	■	■
Color Temperature	3500K, 4000K, 5000K CCT	3000K, 3500K, 4000K, 5000K CCT	3000K, 3500K, 4000K, 5000K CCT	3000K, 3500K, 4000K, 5000K CCT	3500K, 4100K, 5000K CCT
Continuous Row Mounting	■	■	■	■	■
CRI	80 CRI, 90 CRI	80 CRI, 90 CRI	80 CRI, 90 CRI	80 CRI, 90 CRI	80 CRI
Ambient Temperature	35°	30°	30°	30°	40°
LPW	Up to 120	Up to 150+	Up to 145+	Up to 104	90
Fluorescent Replacement	<ul style="list-style-type: none"> 2,200 lumens 1-Lamp 32W T8 Replacement 4,200 Lumens 2-Lamp 32W T8 Replacement 9,000 Lumens 4-Lamp 32W T8 Replacement 	<ul style="list-style-type: none"> 2,500 lumens 2-lamp 17W T8 Replacement 5,000 lumens 2-lamp 32W T8 Replacement 10,000 lumens 4-lamp 32W T8 Replacement 	<ul style="list-style-type: none"> 2,500 lumens 2-lamp 17W T8 Replacement 5,000 lumens 2-lamp 32W T8 Replacement 10,000 lumens 4-lamp 32W T8 Replacement 	<ul style="list-style-type: none"> 2,250 lumens 2-lamp 17W T8 Replacement 4,500 lumens 2-lamp 32W T8 Replacement 9,000 lumens 4-lamp 32W T8 Replacement 	<ul style="list-style-type: none"> 3,500 lumens 2-lamp 32W T8 Replacement 7,300 lumens 4-lamp 32W T8 Replacement
Dimming	■	■	■	■	■
Battery Pack		■	■	■	■

Please use the spec sheet at www.acuitybrands.com when ordering to ensure component compatibility for your desired configuration.



DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

Visit www.lithonia.com for more information