

MASTERS®

ALL CONDITION SOLDERING PASTE



Certified to
NSF/ANSI 61-G

MASTERS® ALL CONDITION SOLDERING PASTE is a petrolatum based paste used for typical sweat soldering. It has excellent wetting properties that allow for smooth flow and reduced voiding. It is lead free and NSF listed for use with potable water systems.

MASTERS® ALL CONDITION SOLDERING PASTE will work on pipe that is:

- Frozen or cold.
- Wet from condensation or thawing.

Directions:

- Clean surface to be soldered.
- Apply paste sparingly to pipe and fitting.
- Heat parts and apply solder (do not overheat).
- Allow to cool and wipe joints clean.

For lead-free NSF61-G fittings we recommend **MASTERS® TINNING FLUX**

Contains Zinc and Ammonium Chloride.
DO NOT store above 110°F (43.3°C).

Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight	
SP057	57 g (2 oz) Jar	12	2.3 lbs	1 kg
SP227	227 g (8 oz) Jar with Brush Top	28	17 lbs	7.7 kg
SP454	454 g (16 oz) Tub	12	13 lbs	5.9 kg
SP20L	20 L (5 gal) Pail	1	47 lbs	21.3 kg

G. F. THOMPSON CO. LTD.

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada

