



MORRIS CAT#: 25-90340 - 25-90342

General Purpose Switching Relays



Features:

- Intended for many applications in air conditioning, refrigeration, heating and general purpose switching
- Replaces Honeywell, WhiteRodgers/RBM & Mars
- Semi-enclosed compact design
- Quiet & reliable operations
- Universal mounting bracket
- Molded terminal numbers and circuit diagram on top of relay
- Dimensions 2.13" × 1.88" × 2.25"
- 2 Pole DT mode
- Temperature Range: -40°C (-40°F) to 54°C (130°F)
- Mechanical Life: 750,000 operations
- Electrical Life: 100,000 operations
- Coil Frequency: 50/60 Hz.
- Coil Insulation: Class B
- Coil Duty Cycle: Continuous
- Terminals: 1/4" quick-connects
- Contact Material: Silver Cadmium oxide
- Enclosure: Phenolic
- UL & cUR (file E44211)

CAT. NO.	COIL VOLTAGE	DESC	TERMINALS 1-2-3	TERMINALS 4-5-6	AMPS	FLA/LRA @125V	FLA/LRA @250V	COIL RESISTANCE	COIL MA	INRUSH VA	HP	UOM	ORDER MULTIPLE
25-90340	24	DPDT	POWER	POWER	15	83/14	41/7	15	334	21.5	3/4	EA	1
25-90341	110/120	DPDT	POWER	POWER	15	83/14	41/7	400	66	21.5	3/4	EA	1
25-90342	208/240	DPDT	POWER	POWER	15	83/14	41/7	1415	38	21.5	3/4	EA	1