



Representative Image

Catalog No. U076C033

Description: MW 100A SURF UNMTRD 50/2-20 GFCI

UPC No 784567571868

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Temporary Power
----------	-----------------

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	14-50WR(BR54UWR) (2) 5-20WR2GFCI
Feed	Overhead
AIC	10,000
Amps	90.0 A
Cabinet Size	9 X 17
Circuit Protection	Yes
Hub Provision	No
Installed Breaker	GFI250 (2) CB120
Load Center	LC55N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	No
Unit Weight	16.0 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------