



Representative Image

Catalog No. U239G

Description: G00A SURFACE UNMTRD 30/20/20

UPC No 784567301243

Home > Power Outlets

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

| | |
|----------|---------------|
| Category | Power Outlets |
|----------|---------------|

Specifications

| | |
|--------------------------------|-----------------------|
| Mounting | Surface |
| Heads | 1 |
| Metering | Unmetered |
| Receptacles | L6-30R L5-20R (x2) |
| Feed | Overhead |
| AIC | 10,000 |
| Amps | 200 A |
| Cabinet Size | 14 in. W X 21 in. H |
| Circuit Protection | Breaker |
| Hub Provision | Yes |
| Installed Breaker | (2) GFI120 GFI230 |
| Load Center | LC1212PC |
| Loop Feed | No |
| Phase | 1 |
| Suitable for Service Equipment | No |
| Unit Weight | 9 lb |
| Volts | 120/240 |

Classifications

| | |
|------------------|-------|
| Standard Package | 1 |
| Stock Class Code | Stock |

Approvals

| | |
|---------------|--------|
| Certification | UL/CUL |
|---------------|--------|