MOEN® OMMERCIAL

DESCRIPTION

- Brass construction with chrome plated finish
- 1/2" IPS connections
- 4" centerset •
- 3-5/8" spout reach

OPERATION

- 4" wrist blade handles with hot and cold color indicators* Smooth handle models have hot and cold color indicator at torx
- head screw
- Vandal resistant torx head screws
- Vandal resistant laminar flow aerator

FLOW

Water usage is limited to these maximum flow rates as indicated by the corresponding product markings

CARTRIDGE

- Brass shell, ceramic disc cartridge •
- 1/4 turn operation

STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372 •
- Products marked with 1.2 gpm & 1.5 gpm are compliant with WaterSense® and California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking ADA 🔄 for lever handles

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the • original consumer purchaser
- 5 year warranty if used in commercial installations





M-Dura[™] **Two-Handle Bar/Pantry Faucet**

Model	Flow (gpm/Lpm)	Handle Style	WaterSense Certified
8278	1.2 / 4.5	Decal	Х
8278SM	2.2 / 8.3	Smooth	
8278SMF12	1.2 / 4.5	Smooth	Х
8278SMF15	1.5 / 5.7	Smooth	Х

NOTE: Designed to be installed through 2 holes - 1" min. dia.





50000141010

SPC11253

01/11/2017