


Specifications



BAMBOO™ Two-Handle Bidet Faucet

Model: TS8815BN

Valve: 9200

NOTE: CANNOT BE USED WITH NON RIM FLUSH **BIDET FIXTURES**

6" (152mm) MIN. 16" (406mm) MAX. 2-7/8" 3" (76mm) MIN. (72mm) DIVERTING 5-1/8" **MECHANISM** (130mm) **HANDLE** 3-1/4" 2-1/2" **ESCUTCHEON DIA.** (83mm) 2" (64mm) (51mm) 1-7/8" (47mm) CRITICAL **LEVEL SPRAY** 1-1/4" (32mm) MAX. NOZZLE **DECK THICKNESS** 2-1/8" 7/8" (53mm) Nozzle (22mm) Diameter HOT COLD MAX. 1-5/8" INLET **FLEXIBLE INLET** (42mm) CONNECTORS **NOTE: MINIMUM DIA. HOLES FOR INSTALLATION** Diverter Valve = 1" (25mm) 3/8" DIA. Handle Valves = 1-1/8" (29mm) LIFT ROD **SUPPLY** Spray Nozzle = 5/8'' (16mm) TUBE Lift Rod Escutcheon = 1/2" (13mm)

CRITICAL DIMENSIONS

(DO NOT SCALE)

DESCRIPTION

- Metal construction with LifeShine® brushed nickel finish
- For installations from 6" (152mm) to 16" (406mm) centers
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing
- Diverter valve includes an integral vacuum breaker

OPERATION

- Lever style handles, 180° rotation
- Rotate hot side handle counterclockwise to open and clockwise to close
- Rotate cold side handle clockwise to open and counterclockwise to close
- Water flow is diverted by turning the knob counterclockwise for fill and clockwise for rosetta spray

CARTRIDGE

- 94831 diverter cartridge
- 1224 cartridge design with nonmetallic/nonferrous and stainless steel material

STANDARDS

- Third party certified to CSA B125.1, ASME A112.18.1, and all applicable requirements referenced therein
- ADA (for lever handle

WARRANTY

Rev. 3/11

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN www.moen.com