



ALL PURPOSE LEAK DETECTOR TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

- Oatey All Purpose Leak Detector is formulated to detect leaks on tubing, valves, cylinders pressure tanks or any other system under air, gas or oxygen pressure.

APPLICATION / USES

- Oatey All Purpose Leak Detector is recommend for use to detect leaks on pipelines, fittings, tanks, pressure vessels, valves and other hard surfaces.

Consult Oatey Technical Department for applications not specifically referenced above.

PHYSICAL PROPERTIES / INGREDIENTS

INGREDIENTS (CAS Number):

Propylene Glycol (57-55-6)

CHEMICAL PROPERTIES

Appearance	Blue Liquid
Odor	Citrus Fragrance
Boiling Point	>160°F (> 71.1°C)
Solubility in Water	Soluble
Specific Gravity	1.017 - 1.058
Shelf Life	1 Year from Mfg. Date

PRODUCT NUMBER	DESCRIPTION	QTY	WEIGHT
30209	8 oz. Leak Detector with dauber	12	8 lbs.
30211	16 oz. Leak Detector with trigger spray	12	17 lbs.
30212	Gallon Leak Detector	4	39 lbs.



DIRECTIONS

Apply All Purpose Leak Detector to the connection to be checked. Watch for bubble clusters around connection. Large leaks will form large bubbles. Small leaks will form a white foam and may take several minutes to form. Do not dilute this product. Use directly from container. Remove excess All Purpose Leak Detector with water spray or wipe of with a damp rag.

PRECAUTIONS

Read all cautions and directions carefully before using this product. Avoid contact with eyes and skin. Use with adequate ventilation. Wash thoroughly after handling. Keep container closed when not in use. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN. Refer to material safety data sheet for more information.

For emergency first aid help, call 1-303-623-5716 COLLECT.