

BBLU-D DIMENSIONS & INSTALLATION TOOLING INFORMATION (CONTINUED)

CATALOG NUMBER	COPPER CONDUCTOR SIZE	STUD HOLE SIZE	FIGURE DIMENSIONS (IN.)						INSTALLATION TOOLING				WIRE STRIP LENGTH
			STUD HOLE SPACING	TONGUE WIDTH "W"	TONGUE LENGTH "C"	TONGUE THICKNESS "T"	BARREL LENGTH "B"	OVERALL LENGTH "L"	COLOR CODE	PENN-UNION DIELESS MECHANICAL TOOLS	BURNDY DIE INDEX NO. /TOOL	PENN-UNION DIE CATALOG NO.	
BBLU-3D-2TC14	3 AWG	1/4"	.63	.65	1.22	.20	1.13	2.60	White	TDM-250 or TDM-500	9	T-9	1-1/4"
BBLU-3D-2TC14E2		1/4"	.75	.65	1.36	.20	1.13	2.74					
BBLU-3D-2TC38E2		3/8"	.75	.65	1.58	.20	1.13	2.96					
BBLU-3D-2TC38E3		3/8"	.81	.65	1.83	.20	1.13	3.21					
BBLU-3D-2TC38		3/8"	1.00	.65	1.83	.20	1.13	3.21					
BBLU-3D		5/16"	.88	.53	1.63	.09	1.13	3.03					
BBLU-2D	2 AWG	5/16"	.75	.59	1.58	.11	1.25	3.11	Brown	TDM-250 or TDM-500	10	T-10	1-5/16"
BBLU-2D-2TC14		1/4"	.63	.59	1.22	.11	1.25	2.75					
BBLU-2D-2TC14E2		1/4"	.75	.59	1.36	.11	1.25	2.89					
BBLU-2D-2TC38E2		3/8"	.75	.59	1.58	.11	1.25	3.11					
BBLU-2D-2TC38E3		3/8"	.81	.59	1.83	.11	1.25	3.36					
BBLU-2D-2TC38		3/8"	1.00	.59	1.83	.11	1.25	3.36					
BBLU-2D-2NTC38		3/8"	1.75	.59	2.58	.11	1.25	4.11					
BBLU-2D6		1/2"	1.75	.81	3.00	.10	1.25	4.53					
BBLU-1D	1 AWG	5/16"	.88	.67	1.63	.11	1.38	3.38	Green	TDM-250 or TDM-500	11	T-11	1-1/2"
BBLU-1D-2TC14		1/4"	.63	.67	1.22	.10	1.38	2.94					
BBLU-1D-2TC14E2		1/4"	.75	.67	1.36	.10	1.38	3.08					
BBLU-1D-2TC38E2		3/8"	.75	.67	1.58	.10	1.38	3.30					
BBLU-1D-2TC38E3		3/8"	.81	.67	1.83	.10	1.38	3.55					
BBLU-1D-2TC38		3/8"	1.00	.67	1.83	.10	1.38	3.55					
BBLU-1D2		1/2"	1.75	.70	2.77	.09	1.20	4.12		-	Y644HS	-	1-5/16"
BBLU-1/0D	1/0 AWG	5/16"	.88	.73	1.59	.13	1.38	3.31	Pink	TDM-250 or TDM-500	12	T-12	1-1/2"
BBLU-1/0D-2TC14		1/4"	.63	.74	1.22	.11	1.38	2.94					
BBLU-1/0D-2TC14E2		1/4"	.75	.74	1.36	.11	1.38	3.08					
BBLU-1/0D-2TC38E2		3/8"	.75	.74	1.58	.11	1.38	3.30					
BBLU-1/0D-2TC38E3		3/8"	.81	.74	1.83	.11	1.38	3.55					
BBLU-1/0D-2TC38		3/8"	1.00	.74	1.83	.11	1.38	3.55					
BBLU-1/0D-2NTC38		3/8"	1.75	.74	2.58	.11	1.38	4.30					
BBLU-1/0D3		1/2"	1.75	.81	3.00	.10	1.38	4.63					
BBLU-2/0D-2TC14	2/0 AWG	1/4"	.63	.82	1.22	.12	1.50	3.06	Black	TDM-250 or TDM-500	13	T-13	1-5/8"
BBLU-2/0D-2TC14E2		1/4"	.75	.82	1.36	.12	1.50	3.20					
BBLU-2/0D-2TC38E2		3/8"	.75	.82	1.58	.12	1.50	3.42					
BBLU-2/0D-2TC38E3		3/8"	.81	.82	1.83	.12	1.50	3.67					
BBLU-2/0D-2TC38		3/8"	1.00	.82	1.83	.12	1.50	3.67					
BBLU-2/0D		1/2"	1.75	.82	3.00	.12	1.50	4.84					
BBLU-3/0D-2TC14	3/0 AWG	1/4"	.63	.89	1.22	.13	1.50	3.13	Orange	TDM-250 or TDM-500	14	T-14	1-5/8"
BBLU-3/0D-2TC14E2		1/4"	.75	.89	1.36	.13	1.50	3.27					
BBLU-3/0D-2TC38E2		3/8"	.75	.89	1.58	.13	1.50	3.49					
BBLU-3/0D-2TC38E3		3/8"	.81	.89	1.83	.13	1.50	3.74					
BBLU-3/0D-2TC38		3/8"	1.00	.89	1.83	.13	1.50	3.74					
BBLU-3/0D		1/2"	1.75	.89	3.00	.13	1.50	4.91					
BBLU-4/0D-2TC14	4/0 AWG	1/4"	.63	1.00	1.22	.14	1.63	3.32	Purple	TDM-250 or TDM-500	15	T-15	1-3/4"
BBLU-4/0D-2TC14E2		1/4"	.75	1.00	1.36	.14	1.63	3.46					
BBLU-4/0D-2TC38E2		3/8"	.75	1.00	1.58	.14	1.63	3.68					
BBLU-4/0D-2TC38E3		3/8"	.81	1.00	1.83	.14	1.63	3.93					
BBLU-4/0D-2TC38		3/8"	1.00	1.00	1.83	.14	1.63	3.93					
BBLU-4/0D-2NTC38		3/8"	1.75	1.00	2.58	.14	1.63	4.68					
BBLU-4/0D-2TC716E2		7/16"	.75	1.00	1.83	.14	1.63	3.93					
BBLU-4/0D		1/2"	1.75	1.00	3.00	.14	1.63	5.10					
BBLU-025D-2TC14E2	250 kcmil	1/4"	.75	1.09	1.36	.16	1.63	3.58	Yellow	TDM-250 or TDM-500	16	T-16	1-3/4"
BBLU-025D-2TC38E3		3/8"	.81	1.09	1.83	.16	1.63	4.05					
BBLU-025D-2TC38		3/8"	1.00	1.09	1.83	.16	1.63	4.05					
BBLU-025D		1/2"	1.75	1.09	3.00	.16	1.63	5.13					
BBLU-030D-2TC14E2	300 kcmil	1/4"	.75	1.19	1.36	.16	2.00	3.95	White	TDM-500	17	T-17	2-1/8"
BBLU-030D-2TC38		3/8"	1.00	1.19	1.83	.16	2.00	4.42					
BBLU-030D		1/2"	1.75	1.19	3.00	.16	2.00	5.59					

CONTINUED ON PAGE 26