

Aluminum Clear/Black Pre-Insulated Power Bars Double-Sided Conductor Entry

Type IPB-D/Type IPBB-D

Manufactured from high strength aluminum alloy

Dual rated for aluminum and copper conductors, 600 Volt, 90°C

Wide conductor range: 750 kcmil - 14 Sol.

- Allows flexibility in the field and reduces number of connectors in inventory

Multiple conductor configurations: 2 through 14 position

- Choose the right connector for the application

Double sided configuration allows conductors to be installed from either side of connector



Suitable for use in panelboards, cable trays, raceways, ducts and troughs

Pre-filled with oxide inhibitor, prevents oxidation, moisture and contaminants from entering contact area

Supplied with removable access plugs over screw and conductor ports providing protection against contaminants

Pre-insulated at factory with high dielectric strength plastisol

- Black insulation is UV resistant
- Clear insulation allows for visual confirmation that conductor is properly inserted
- Saves time, eliminates taping, reduces overall installation costs
- Abrasion and chemical resistant
- Will not support combustion



DOUBLE SIDED ENTRY



CLEAR PART NO.	BLACK PART NO.	NUMBER OF CONDUCTORS	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)			HEX SIZE
				L	W	H	
IPB-NA4-2D	IPBB-NA4-2D	2	4 Str - 14 Sol.	1.39	1.5	1.25	1/8
IPB-NA4-3D	IPBB-NA4-3D	3		1.99	1.5	1.25	
IPB-NA4-4D	IPBB-NA4-4D	4		2.59	1.5	1.25	
IPB-NA4-5D	IPBB-NA4-5D	5		3.19	1.5	1.25	
IPB-NA4-6D	IPBB-NA4-6D	6		3.79	1.5	1.25	
IPB-NA4-8D	IPBB-NA4-8D	8		4.99	1.5	1.25	
IPB-NA4-10D	IPBB-NA4-10D	10		6.19	1.5	1.25	
IPB-NA4-12D	IPBB-NA4-12D	12		7.39	1.5	1.25	
IPB-NA4-14D	IPBB-NA4-14D	14		8.59	1.5	1.25	
IPB-NA2/0-2D	IPBB-NA2/0-2D	2	2/0 Str - 14 Sol.	1.64	1.56	1.38	3/16
IPB-NA2/0-3D	IPBB-NA2/0-3D	3		2.37	1.56	1.38	
IPB-NA2/0-4D	IPBB-NA2/0-4D	4		3.09	1.56	1.38	
IPB-NA2/0-5D	IPBB-NA2/0-5D	5		3.82	1.56	1.38	
IPB-NA2/0-6D	IPBB-NA2/0-6D	6		4.54	1.56	1.38	
IPB-NA2/0-8D	IPBB-NA2/0-8D	8		5.99	1.56	1.38	
IPB-NA2/0-10D	IPBB-NA2/0-10D	10		7.44	1.56	1.38	
IPB-NA2/0-12D	IPBB-NA2/0-12D	12		8.89	1.56	1.38	
IPB-NA2/0-14D	IPBB-NA2/0-14D	14		10.34	1.56	1.38	