

Bronze Service Post Connectors

Type SSS and SCS

Male design

- Manufactured from high copper content wrought alloy for maximum conductivity
- Designed to ground one or two cables to steel structures, bus bars, or transformers
- True hex design for body and nut simplifies installation with standard socket, box, or open end wrenches
- Split bolt design provides maximum conductor pull-out performance
- UL listed for use as a power connector per UL486A-B and for grounding and bonding applications per UL467
- Suitable for direct burial in earth or concrete
- Suffix "-A1" for 1/2" longer mounting stud
- For stud mounting hardware, suffix catalog number with "-SMH"



Type SCS



Type SSS



Type SSS-A1



CATALOG NUMBER	CONDUCTOR RANGE	CATALOG NUMBER	CONDUCTOR RANGE	APPROXIMATE DIMENSIONS (IN.)				
				STUD THREAD SIZE	NUT HEX	C	H	BODY HEX
FIG. 1 (ONE CABLE)		FIG. 2 (TWO CABLES)						
SSS-0	12 Sol. - 8 Str.	SCS-0	12 Sol. - 8 Str.	1/4-20	1/2	.50	.63	3/8
SSS-0A1		SCS-0A1				1.00		
SSS-1	8 Sol. - 7 Str.	SCS-1	10 Sol. - 7 Str.	1/4-20	11/16	.50	.88	1/2
SSS-1A1		SCS-1A1				1.00		
SSS-2	10 Sol. - 4 Str.	SCS-2	10 Sol. - 4 Str.	5/16-18	3/4	.56	.94	9/16
SSS-2A1		SCS-2A1				1.00		
SSS-3	6 Sol. - 3 Str.	SCS-3	10 Sol. - 3 Str.	3/8-16	13/16	.63	1.06	5/8
SSS-3A1		SCS-3A1				1.13		
SSS-4	4 Str. - 2 Str.	SCS-4	10 Sol. - 2 Str.	3/8-16	7/8	.63	1.06	11/16
SSS-4A1		SCS-4A1				1.13		
SSS-5	6 Sol. - 1/0 Str.	SCS-5	2 Sol. - 1/0 Str.	1/2-13	1	.75	1.31	3/4
SSS-5A1		SCS-5A1				1.25		
SSS-6	1 Sol. - 2/0 Str.	SCS-6	2 Sol. - 2/0 Str.	1/2-13	1 1/8	.75	1.44	7/8
SSS-6A1		SCS-6A1				1.25		
SSS-8	3/0 Sol. - 4/0 Str.	SCS-8	1 Sol. - 4/0 Str.	5/8-11	1 3/8	1.00	1.69	1 1/8
SSS-8A1		SCS-8A1				1.50		
SSS-9	4/0 Str. - 350 kcmil	SCS-9	1 Str. - 350 kcmil	5/8-11	1 1/2	1.00	2.00	1 1/4
SSS-9A1		SCS-9A1				1.50		
SSS-10	250 - 500 kcmil	SCS-10	3/0 Str. - 500 kcmil	3/4-10	1 13/16	1.38	2.31	1 1/2
SSS-10A1		SCS-10A1				1.75		
*SSS-11	300 - 750 kcmil	*SCS-11	350 - 750 kcmil	3/4-10	2 1/4	1.38	2.50	1 7/8
*SSS-11A1		*SCS-11A1				1.88		
*SSS-12	750 - 1000 kcmil	*SCS-12	500 - 1000 kcmil	1-8	2 5/8	1.50	3.00	2 3/8
*SSS-12A1		*SCS-12A1				2.00		

*UL listing is limited to 500 kcmil




FIG. 1




FIG. 2