


Pfirst Series™ Kitchen Faucet

- | | |
|--|--|
| G136-2000 Finish(C) <input type="checkbox"/> | G136-5000 Finish(C) <input type="checkbox"/> |
| G136-200S Finish(S) <input type="checkbox"/> | G136-500S Finish(S) <input type="checkbox"/> |
| G136-200Y Finish(Y) <input type="checkbox"/> | G136-500Y Finish(Y) <input type="checkbox"/> |



Specifications

Features

- 1.75 GPM Flow Rate
- Lever Handle
- 3-Hole Installation (200* Only)
- 4-Hole Installation (500* Only)
- High Arc Spout
- Includes Matching Side Spray (500* Only)
- Chrome Side Spray (5000 Only)
- Stainless Steel Side Spray (500S Only)
- Pforever Seal Ceramic Disc Valves
- Pforever Warranty®

- Two-Handle
- 3 or 4-Hole Installation
- Pforever Seal

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- NSF 61/9 Annex G (Low lead)
- Cal Green Compliant
- CEC Compliant
- ADA Compliant-ANSI A117.1 (Lever handles only)



Dimensions

