



Core & Coil (71A) HPS ~GT~ 400W

CORE & COIL HID HPS BAL 600W S106 120/208/240V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	S106			
Lamp Type	600W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	CWA			
Ballast Type	Magnetic HID			
Base Model	71A85E5			
Core Size	4 1/4 x 6			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI561-H5			
Ignitor Temperature Rating	105°C			
Capacitor Value	64 MFD			
Capacitor Catalog Number	7C640S28RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	3.15 in			
Capacitor Height	5.10 in			
Automatic Restart	No			

Operating and Electrical				
Input Voltage	120/208/240 V			
Input Frequency	60 Hz			
Inp. Current (Open Circuit)	3/1.75/1.6 A			
Input Current (Starting)	5.25/3/2.6 A			
Input Current (Short Circuit)	3.3-5/1.9-2.8/1.6-2.4 A			
Secondary Short Circuit Current	7.4-9 A			
Constant Wattage Deviation	Within Trapezoid			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Nominal Open Circuit Voltage	220 V			
Input Current (Operating) (Nom)	5.5/3.25/2.85 A A			
Input Power (Nom)	670 W			
Rated Lamp Watts	600 W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length by Color	12"			
Wire Type	Stranded			
Remote Wiring Configuration Allowed	Yes			


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) HPS ~GT~ 400W

Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	15/9/8 A
Approval and Application	
Open Circuit Voltage Test (Volts)	200-245 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A/A/B
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029B

Product Data	
Order product name	CORE & COIL HID 71A85E5500D
EAN/UPC - Product	781087042670
Order code	71A85E5500D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	913700578109
Net Weight (Piece)	10.575 kg

Dimensional drawing



HPS BAL 600W S106 120/208/240V C&C

Product	C1	C2	A1	A2	A3	B1	B2
CORE & COIL HID 71A85E5500D	5.10 in	3.15 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

