



Reflector Flood

500R40/3FL 120/130V 24/1

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These flood lamps produce homogeneous beams of high intensity for general illumination.


Product data

General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	Universal [Universal]
Main Application	Indoor Reflector
Gas Filling	GAS
Footnote Incandescent 1	Light output is maintained best when operated within 45 degrees vertically of base up. (51)
Footnote Incandescent 2	The bulb, though made of heat resistant glass, may break if moisture falls on it. Not recommended for use in enclosed, close-fitting housings. (53)
Footnote Incandescent 3	Circle E-The encircled E means this bulb meets Federal minimum efficiency standards.
Light Technical	
Beam Description	Flood [Flood]
Operating and Electrical	
Power (Rated) (Nom)	500 W
Voltage (Nom)	120-130 V

Mechanical and Housing	
Bulb Finish	Frosted (FR)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Filament Shape	CC11 [V-shape above glass button (cylindriform)]
Approval and Application	
Approbation Marks	Circle E logo
Product Data	
Order product name	500R40/3FL 120/130V 24/1
EAN/UPC - Product	046677144340
Order code	144345
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	920673735502
Net Weight (Piece)	0.001 kg

Reflector Flood

Dimensional drawing



Product	D	C (max)
500R40/3FL 120/130V 24/1	4.838 in	7.25 in

500W E39 120-130V R40 FL

