



Ceramalux ALTO

C400S51/ALTO 12PK

These lamps pass the EPA's TCLP test for non-hazardous materials. Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data


General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Bulb Shape	ED18 [ED18]
Operating Position	Universal [Universal]
Main Application	General and Street Lighting
ANSI Code HID	S51
Features	ALTO® (ALTO)
Light Technical	
Luminous Flux (Rated) (Min)	45000 lm
Luminous Flux (Rated) (Nom)	50000 lm
Photosynthetic Photon Flux (PPF)	595 µmol/s
Design Mean Lumens	45000 lm
Chromaticity Coordinate X (Nom)	515
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (rated) (Min)	112.5 lm/W
Luminous Efficacy (rated) (Nom)	125 lm/W
Color Rendering Index (Nom)	21
Operating and Electrical	
Lamp Current (Nom)	4.6 A
Ignition Supply Voltage (Max)	198 V
Re-ignition Time (Min) (Max)	1 min

Ignition Time (Max)	5 s
Voltage (Max)	115 V
Voltage (Min)	84 V
Voltage (Nom)	100 V
Mechanical and Housing	
Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Approval and Application	
Picogram Per Lumen Hour	26.4 pg/lm.h
Mercury (Hg) Content (Max)	23.5 mg
UV	
Pet (Niosh) (Nom)	353 h/500lx
Damage Factor D/fc (Nom)	0.03
Luminaire Design Requirements	
Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	210 °C
Product Data	
Order product name	SON 400W E39 ED58 CL SLV/12

EAN/UPC - Product	046677368814
Order code	368811
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material Nr. (12NC)	928601139301
Net Weight (Piece)	0.187 kg

Dimensional drawing



Product
SON 400W E39 ED58 CL SLV/12

HPS 400W E39 ED18 U ALTO

