



SL2-LED20

LED Strip Light

SPECIFICATIONS

| | |
|---------------------------|--|
| Watts | 20 |
| Lumens | 2448 |
| Efficacy | 121.4 Lm/W |
| Replaces Up To | 2 Lamp T8 17W |
| Colour Temp** | Selectable - 3K, 4K, 5K |
| Certification | cULus, IP20 |
| Operating Temp | -30°C to +40°C |
| Voltage | 120-347V |
| LED Life (L70) | >100,000 hours |
| Housing Material | Steel |
| Lens Material | Polycarbonate |
| Lens Type | Frosted |
| Mounting | Surface mount, suspended mount using linear ceiling pendant mount kit. |
| Total Harmonic Distortion | 5% |
| Power Factor | 0.99 |
| CRI | 80 |
| Internal Surge Protection | 2KV |
| Weight | 2.8 lbs |

**Colour temperature is selectable and can be adjusted on the fixture through a switch. The default switch setting is set to 4K on the fixture.



DESCRIPTION

The SL2-LED20 strip light provides a highly efficient lumen output of approx. 2400 lumens ideal for replacing 2 Lamp T8 17W fixtures. The frosted linear lens provides uniform light distribution ideal for use in shops, coves and general area lighting.

APPLICATIONS



Shops



Cove Lighting




General Area Lighting

FEATURES


- Fixture can be set at a colour temperature of 3000K, 4000K or 5000K while installing through a switch inside the housing
- Narrow, linear design with frosted lens for uniform light distribution
- Join up to 35 fixtures on a single circuit using easy connector steel plates. NOTE: Fixtures are daisy chained with line wires fished through the housing continuous row.
- Options: Dimming high frequency motion sensor, remote control, wire cage, reflector wings, linear ceiling pendant mount kit.
- Optional factory-installed smart lighting control available: Lutron Athena Wireless smart control allows zone and control changes digitally and wirelessly.

DIMENSIONS




Keyholes for
suspended/ceiling
mounting

COLOUR SELECTABLE SWITCH



1. 5000K
2. 4000K
3. 3000K



Easily change the colour temperature with the flip of a switch.

1. TOP position = 5000K
2. MIDDLE position = 4000K
3. BOTTOM position = 3000K

The switch is located
inside of the fixture.

LINEAR CEILING PENDANT MOUNT KIT


Linear Ceiling Pendant Mount Kit

Contains 2 x 5 foot aircraft cables with ceiling mounting plates, fixture mounting rod and nut, 6 drywall anchors, and 6 screws.

SKU 089814




REFLECTOR WINGS



Reflector Wings Kit - Wings attach by inserting tabs into the cutouts on the fixture
SKU 099560

WIRE CAGE




Wire Cage - To install, place wire cage over the fixture and screw the clips on to the mounting surface.
SKU 002270

DHFS MOTION SENSOR

Dimming High Frequency Motion Sensor is factory installed.

| BRIGHTNESS | SENSITIVITY | HOLD TIME | DAYLIGHT SENSOR | STAND-BY DIM | STAND-BY TIME |
|------------|-------------|-----------|-----------------|--------------|---------------|
| 100% | 100% | 5 minutes | Disabled | DIM: 30% | 60 minutes |

RC100 REMOTE




** Required additional purchase for custom configurations

DHFS SENSOR SPECIFICATIONS

| | |
|-------------------------------|---|
| POWER SUPPLY | 100-277 VAC, SINGLE PHASE, 60HZ 100-347 VAC, SINGLE PHASE, 60HZ 208/230/480 VAC, PHASE TO PHASE, 60HZ |
| MAXIMUM LOAD | 100-120 VAC, 800W, TUNGSTEN 100-120 VAC, 800W, ELECTRONIC BALLAST/LED DRIVER 230-240 VAC, 300W, ELECTRONIC BALLAST/LED DRIVER 277 VAC, 1200W, ELECTRONIC BALLAST/LED DRIVER 347 VAC, 1200W, ELECTRONIC BALLAST/LED DRIVER 480 VAC, 480W, ELECTRONIC BALLAST/LED DRIVER |
| HIGH FREQUENCY SYSTEM | 5.8GHZ +/-75MHZ |
| DIM CONTROL OUTPUT | 0-10V DC DIMMING, 25MA |
| DETECTION RADIUS/ANGLE | MAX 8M (26FT) AT 360° |
| MOUNTING HEIGHT | MAX 6M (20FT) |
| HUMIDITY | MAX 95% RELATIVE HUMIDITY |
| OPERATING TEMP. | -40°C TO +70°C |
| CYCLES | 200,000 ON/OFF CYCLES |
| CERTIFICATIONS | CRUUS, FCC |
| PROGRAMMING | WIRELESS PROGRAMMING USING RC-100 REMOTE |

DHFS DETECTION RANGE & RADIUS/ANGLE




SL2-LED20-B-4K-DIM(SL2-LED20-B-VK-DIM MOUNTED AT 8 FEET

Total Lumens = 2448

Mounting Height = 8 Ft

Maximum Calculated Value = 11.55 Fc



ORDERING GUIDE

| SL2 | LED20 | H | VK | DIM | |
|-------|---------------|--|----------------------|---|--|
| WATTS | VOLTAGE | COLOUR TEMP. | DRIVER | CONTROLS | |
| | H - 120-347V* | VK - Colour Selectable (can be adjusted to 3K, 4K, or 5K) | DIM - 0-10V Dimming* | BLANK - No Controls* | |
| | | | | DHFS - Dimming High Frequency Sensor (factory installed inside the housing) | |
| | | | | AWN - LUTRON SMART CONTROL** | |

*Standard Configuration.

**Factory installed Lutron Athena Wireless Node with RF only (A-WN-D01-RF-WH). Gateway and controller not included.

FIELD INSTALLED ACCESSORIES

CHECK THE ACCESSORIES YOU WISH TO ORDER:

- 089814 LINEAR CEILING PENDANT MOUNT KIT
- 002270 SL2-LED WIRE CAGE
- 099560 SL2-LED REFLECTOR WINGS KIT - WHT
- 087016 RC-100 MOTION SENSOR REMOTE CONTROL