

## RTP™ SERIES Condensate Removal Tank Pumps

### Description

The RTP (RectorSeal Tank Pump) series is designed as an automatic condensate removal pump for heating and air conditioning systems. The pump is controlled by a float switch mechanism which turns the pump on when approximately 2¼" of water collects in the tank, and automatically switches off when the tank drains to approximately 1¼".



### Packaging

Code	Description	Qty per Case	Lbs per Case	Cubic Feet
83885	RTP15-110	10	57.3	3.57
83886	RTP15-230	10	57.3	3.57
83887	RTP24-110	10	57.3	3.57
83888	RTP24-230	10	57.3	3.57

### Applications

Air conditioners, furnaces and dehumidifiers, residential or commercial

### Characteristics | Features

- ½ gallon high impact ABS tank for durability
- Float arm design for reliable operation
- 3 inlet drain holes for easy drain hose access
- Compact design for easy installation
- 6 foot power cord to easily position pump
- 10 inch wires to connect pump to furnace or air handler for system shutoff capability
- Thermal overload protection
- Removable 3/8" check valve
- One-year limited warranty

### Specifications

Product code	Model Name	Volts	Hertz	Running		Gallons/Liters Per Hour at Height			Shutoff
				Amps	Watts	1 ft / .3m	5 ft / 1.5 m	9 ft / 2.7 m	
83885	RTP15-110	110	60	1	60	66 gph; 250 lph	53 gph; 200 lph	40 gph; 150 lph	15 ft / 4.6 m
83886	RTP15-230	230	50/60	.6 / .45	60 / 50	69/66 gph; 260/250 lph	61/53 gph; 230/200 lph	45/40 gph; 170/150 lph	15 ft / 4.6 m
83887	RTP24-110	110	60	2.2	110	153 gph; 580 lph	137 gph; 520 lph	124 gph; 470 lph	24 ft / 7.3 m
83888	RTP24-230	230	50/60	1.3 / 1.1	125 / 110	140/153 gph; 530/580 lph	127/137 gph; 480/520 lph	111/124 gph; 420/470 lph	24 ft / 7.3 m

## LIMITED WARRANTY

RectorSeal, LLC (“RectorSeal”) warrants the following:

### 1. LIMITED WARRANTY

The Product subject to this sale will be of good quality and workmanship and conform to the Product’s performance specifications. If during the Warranty Period, the purchaser believes that a Product covered under this Limited Warranty fails to conform to specifications or is defective by reason of faulty design, workmanship or materials, then the purchaser must promptly notify RectorSeal within 15 days of such determination (a “Defect Notice”). RectorSeal will then inspect the Product and determine, in its reasonable judgment, whether an adjustment, repair, or replacement of the Product is warranted, and if so, promptly make the adjustment, repair, or replacement at no additional charge to the purchaser.

RectorSeal may elect to repair the Product on site or have the Product returned to RectorSeal’s premises. If the Product is returned to RectorSeal, risk of loss to the Product will at all times remain with the purchaser, and shipping costs will be borne by RectorSeal where the Product defect is covered by this Limited Warranty.

The foregoing Limited Warranty will be voided in the following conditions:

- I. The Product has not been used or stored (with proper documentation) in a manner consisted with the operating and maintenance instructions of RectorSeal or in compliance with the use or proper purpose intended by RectorSeal (i.e the Product was connected to voltage other than indicated on the nameplate, the Product was allowed to operate dry (fluid supply cut off), the Product was used to circulate anything other than water, etc.);
- II. The installation or application of the Product has not been performed in accordance with RectorSeal’s instructions (i.e. the Product cord was cut off to a length less than 3 feet);
- III. The Product defect has been caused by fire, accident, abuse, misuse (i.e. the Product’s sealed motor housing has been opened), unauthorized alteration, repair, reconstruction or maintenance (including modification of labels or packaging) or the use of sub-standard consumables (ordinary wear and tear excepted);
- IV. The Product defect has arisen from a design, specification, component or material supplied by or on behalf of the purchaser or a third party; or
- V. The Product or any part of the Product has been used or combined with goods, products, hardware or other materials, or has been replaced with a part not supplied or approved by RectorSeal.

### 2. LIMITED WARRANTY TERM

The duration of this Limited Warranty is 12 months from the Product’s date of sale (the “Warranty Period”).

### 3. LIMITATION OF LIABILITY AND DISCLAIMER

Before using the Product, the purchaser is solely responsible for determining the suitability of the Product for the intended use, and the purchaser assumes all risk and liability whatsoever in connection therewith. The terms set forth herein are the purchaser’s exclusive remedy for breach of this Limited Warranty. RectorSeal does not warrant any products or services not provided by RectorSeal, or any third-party products or services that incorporate the Products. **RectorSeal will not under any circumstances be liable for any consequential, incidental, special or punitive damages or losses, whether direct or indirect.**

**EXCEPT FOR THE LIMITED WARRANTY SET FORTH HEREIN, RECTORSEAL MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE PRODUCT, INCLUDING (A) WARRANTY OF MERCHANTABILITY; OR (B) WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, WHETHER EXPRESS OR IMPLIED, BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE.**

Manufactured for

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**  
3255 Wyandotte St. East, Windsor, ON N8Y 1E9, 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor’s and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50633-0720