



A CSW Industrials Company

## PRODUCT DATA SHEET

### D-FACTOR™

High strength cleaner & degreaser

#### Description

D-Factor is an extra strong, heavy duty cleaner. Detergent-based formula rapidly removes grime, oil, grease and dust. Low foaming action cleans grease and dust from surfaces which are normally inaccessible. D-Factor is biodegradable and can be used for cleaning electronic and permanent air filters and all mechanical equipment. D-Factor's maximum degreasing, high strength cleaning formula is self-rinsing and suitable for both condenser and evaporator coils.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

#### Directions for Use:

1. Appropriately dilute with water for economic use.  
**For extremely dirty coils/equipment** - 1 part D-FACTOR to 4 parts water.  
**For cleaning all types of filters** - 1 part D-FACTOR to 4 parts water.  
**For medium dirty coils** -1 part D-FACTOR to 6 parts water.  
**For light dirt removal** -1 part D-FACTOR to 8 parts water.  
**For no-rinse indoor coils** -1 part D-FACTOR to 40 parts water.
2. Shut off system.
3. Apply the diluted solution with a trigger sprayer, hand powered tank or high pressure washer. Use a brush to help faster penetration of hard, encrusted dirt.
4. Allow 5 to 15 minutes soaking time before rinsing. On an operating evaporator coil, rinsing is not required since the condensate will flush out all the loosened slime and dirt.
5. For condenser coils, rinse coil thoroughly with low-pressure washer. Repeat if necessary.



#### Characteristics | Features

- Max degreasing strength
- High cleaning strength
- Biodegradable
- Low foaming
- Concentrated – dilute with water for economical use
- Will not harm copper or aluminum
- Multipurpose

#### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
11060	Gallon (3.8 L)	4 Bottles	45	1.21

## Specifications

Wt/Gal @ 77°F	10 lbs./gal.
Flash Point	None
Color	Yellow
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



## DANGER!

Causes severe skin burns and serious eye damage. May cause respiratory irritation. May be corrosive to metals.

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.**

**Contains: Potassium Hydroxide (CAS# 1310-58-3) and Sodium metasilicate (CAS# 6834-92-0).** May cause respiratory irritation. Harmful to aquatic life.  
**Precautionary Statements: PREVENTION:** Keep only in original container. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. **RESPONSE - IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Take off all contaminated clothing immediately. Rinse skin with water/shower. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. **STORAGE:** Store locked up. Store in corrosive resistant stainless steel container with a resistant inner liner. **DISPOSAL:** Dispose of contents/ container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50400-0420